

DAILY DRILLING REPORT (SYNTHETIC)

OIL-KMC-012 - Kumchai-012

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Kumchai / Girujan
Report Timestamp	2002-06-07 18:00:00
Current Depth	2404.0 m
Mud System	KCl Polymer WBM
Well Risk	Low (41.6/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
06-02 04:29	2298	2780	258	74	10.89	825/784	14.6	Recovery
06-02 19:19	2310	3042	273	107	11.06	853/891	12.0	Normal
06-03 10:09	2322	2956	216	110	11.17	740/742	10.5	Normal
06-04 00:59	2333	3057	226	109	11.12	752/769	11.2	Normal
06-04 15:49	2345	2955	275	118	11.03	760/757	10.8	Normal
06-05 06:39	2357	2824	257	108	11.16	794/768	10.9	Normal
06-05 21:29	2369	3029	236	113	11.11	781/782	13.5	Normal
06-06 12:19	2380	3061	265	106	11.06	762/763	13.1	Normal
06-07 03:09	2392	2937	253	117	11.22	792/799	10.3	Normal
06-07 18:00	2404	2960	254	122	11.47	731/717	6.0	Normal

Operational Events / Lessons

Torque Spike (High) at 1822 m: Torque Spike at 1822 m in Girujan. Sharp torque excursion occurred with RPM instability. Paused drilling to verify BHA behaviour. Outcome: Rotary stability recovered after reaming. Torque 325 kNm, drag 12.6 t, ROP 8.9 m/h. Recommended action: Set warning on rapid torque rise with RPM instability

NPT (Medium) at 1966 m: NPT at 1966 m in Girujan. ROP dropped to zero during equipment unavailability. Switched to standby system where available. Outcome: Operational hold cleared after checks. Recommended action: Track recurring NPT cause by rig and equipment family

Mud Loss (Low) at 1989 m: Mud Loss at 1989 m in Girujan. Partial returns observed at shale shaker. Prepared graded lost-circulation pill. Outcome: Full returns restored and drilling resumed. Flow balance: 726/655 LPM (in/out); pit change -4.6 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Torque Spike (Medium) at 2286 m: Torque Spike at 2286 m in Girujan. Sharp torque excursion occurred with RPM instability. Reduced WOB and RPM. Outcome: Drilling resumed at reduced mechanical loading. Torque 349 kNm, drag 15.7 t, ROP 10.7 m/h. Recommended action: Compare live torque derivative with offset-well baseline

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.