

DAILY DRILLING REPORT (SYNTHETIC)

OIL-MRN-002 - Moran-002

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Moran / Tipam
Report Timestamp	2005-07-29 18:00:00
Current Depth	2545.0 m
Mud System	Glycol-PHPA WBM
Well Risk	Moderate (44.2/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
07-25 20:31	2373	3035	212	113	11.50	784/782	7.9	Normal
07-26 06:54	2392	2999	270	120	11.27	840/833	15.2	Normal
07-26 17:17	2411	3002	229	112	11.12	830/823	13.1	Normal
07-27 03:40	2430	3035	232	104	11.26	854/873	10.1	Normal
07-27 14:04	2450	3063	257	114	11.22	805/801	10.7	Normal
07-28 00:27	2469	3183	261	107	11.35	783/804	7.5	Normal
07-28 10:50	2488	3115	253	100	11.09	824/841	13.3	Normal
07-28 21:13	2507	3234	268	105	11.25	812/832	7.7	Normal
07-29 07:36	2526	2969	226	105	11.31	737/750	8.5	Normal
07-29 18:00	2545	3181	274	96	11.40	781/761	12.2	Normal

Operational Events / Lessons

Mud Loss (Medium) at 1593 m: Mud Loss at 1593 m in Tipam. Flow-out dropped below flow-in with pit loss. Prepared graded lost-circulation pill. Outcome: Loss rate reduced to acceptable level. Flow balance: 708/624 LPM (in/out); pit change -7.8 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Mud Loss (Critical) at 1732 m: Mud Loss at 1732 m in Tipam. Active pit volume declined during stable pump rate. Prepared graded lost-circulation pill. Outcome: Full returns restored and drilling resumed. Flow balance: 712/538 LPM (in/out); pit change -13.5 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Mud Loss (Medium) at 2161 m: Mud Loss at 2161 m in Tipam. Flow-out dropped below flow-in with pit loss. Reduced ROP and conditioned the hole. Outcome: Full returns restored and drilling resumed. Flow balance: 801/665 LPM (in/out); pit change -7.8 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Mud Loss (Medium) at 2315 m: Mud Loss at 2315 m in Tipam. Active pit volume declined during stable pump rate. Reduced pump rate and monitored active pits. Outcome: Circulation stabilized after treatment. Flow balance: 828/703 LPM (in/out); pit change -8.8 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.