

DAILY DRILLING REPORT (SYNTHETIC)

OIL-NHK-002 - Nahorkatiya-002

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Nahorkatiya / Tipam
Report Timestamp	2001-08-30 18:00:00
Current Depth	2606.0 m
Mud System	Glycol-PHPA WBM
Well Risk	High (60.8/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
08-25 22:33	2526	3069	210	105	11.16	804/799	9.0	Normal
08-26 11:22	2535	3211	257	110	11.31	783/791	9.7	Normal
08-27 00:12	2544	3027	260	117	11.16	849/840	10.6	Normal
08-27 13:02	2552	3128	245	109	11.40	840/860	11.2	Normal
08-28 01:51	2561	3176	249	106	11.53	821/824	10.4	Normal
08-28 14:41	2570	3133	277	104	11.41	790/832	6.8	Normal
08-29 03:31	2579	3185	276	112	11.38	811/824	10.8	Normal
08-29 16:20	2588	3262	240	104	11.29	736/717	11.9	Normal
08-30 05:10	2597	3141	285	115	11.47	780/788	10.5	Normal
08-30 18:00	2606	3130	223	119	11.37	744/735	9.5	Normal

Operational Events / Lessons

Torque Spike (Low) at 2248 m: Torque Spike at 2248 m in Tipam. Rotary speed fluctuated during constant pump rate. Reamed short interval and circulated cuttings. Outcome: Spike cleared with no equipment damage. Torque 262 kNm, drag 14.9 t, ROP 11.4 m/h. Recommended action: Reduce WOB/RPM proactively near correlated torque-spike depth

Stuck Pipe (Low) at 2356 m: Stuck Pipe at 2356 m in Tipam. Torque and drag increased while ROP declined. Reduced WOB and increased hole-cleaning circulation. Outcome: BHA freed and hole conditioned before drilling resumed. Torque 302 kNm, drag 24.1 t, ROP 7.6 m/h. Recommended action: Plan preventive wiper trip near analogous interval

Mud Loss (High) at 2445 m: Mud Loss at 2445 m in Tipam. Active pit volume declined during stable pump rate. Prepared graded lost-circulation pill. Outcome: Interval drilled through with controlled losses. Flow balance: 874/651 LPM (in/out); pit change -12.0 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Kick (High) at 2508 m: Kick at 2508 m in Tipam. Unexpected background gas rise preceded influx. Circulated influx under controlled conditions. Outcome: Operations resumed after well-control verification. Gas 195 units; pit change +7.2 bbl; mud weight 11.20 ppg. Recommended action: Raise kick advisory when flow-out exceeds flow-in with rising gas

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.