

DAILY DRILLING REPORT (SYNTHETIC)

OIL-RDS-009 - Rudrasagar-009

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Rudrasagar / Barail
Report Timestamp	2017-12-12 18:00:00
Current Depth	2696.0 m
Mud System	KCl Polymer WBM
Well Risk	Moderate (54.4/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
12-06 23:49	2575	3167	302	108	11.60	766/779	11.6	Normal
12-07 15:11	2588	3348	276	117	11.40	761/759	9.1	Normal
12-08 06:32	2602	3223	229	113	11.42	709/712	11.8	Normal
12-08 21:53	2615	3220	273	104	11.31	741/758	12.4	Normal
12-09 13:14	2629	3264	283	116	11.45	852/848	14.5	Normal
12-10 04:35	2642	3235	245	115	11.32	794/809	14.2	Normal
12-10 19:56	2656	3058	267	104	11.54	785/782	13.6	Normal
12-11 11:17	2669	3201	280	124	11.46	732/718	11.8	Normal
12-12 02:38	2683	3428	261	109	11.43	810/804	13.9	Normal
12-12 18:00	2696	3306	223	95	11.53	725/712	15.3	Normal

Operational Events / Lessons

Mud Loss (Medium) at 1583 m: Mud Loss at 1583 m in Barail. Partial returns observed at shale shaker. Reduced pump rate and monitored active pits. Outcome: Full returns restored and drilling resumed. Flow balance: 849/739 LPM (in/out); pit change -7.6 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

NPT (Critical) at 1932 m: NPT at 1932 m in Barail. Drilling parameters were stable but operations were suspended. Recorded downtime cause and maintenance action. Outcome: Equipment restored and drilling resumed. Recommended action: Track recurring NPT cause by rig and equipment family

NPT (Low) at 2180 m: NPT at 2180 m in Barail. Rotary and WOB remained at zero during downtime. Switched to standby system where available. Outcome: Operational hold cleared after checks. Recommended action: Use offset NPT history in operational readiness review

Mud Loss (Medium) at 2290 m: Mud Loss at 2290 m in Barail. Intermittent circulation losses developed while drilling ahead. Reduced pump rate and monitored active pits. Outcome: Circulation stabilized after treatment. Flow balance: 814/757 LPM (in/out); pit change -2.9 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.