

WELL COMPLETION REPORT (SYNTHETIC)

OIL-BGJ-005 - Baghjan-005

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000057
Field / District	Baghjan / Tinsukia
Block	OALP-IV-03
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2005-10-18 / 2005-12-29
Measured / TVD	2232 m / 2218 m
Trajectory	Vertical; inc 0.9 deg; az 305.0 deg
Formation Interval	1018-1645 m
Lithology	Fluvial sandstone with clay streaks
Pore Pressure Reference	1975 psi
Fracture Gradient	14.94 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	Low (34.4/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	558	Surface
9 5/8 in casing	1294	Intermediate
7 in liner/casing	1964	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2005-10-26 384 m	Kick	High	Pit gain and flow with pumps off were observed. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2005-12-03 1513 m	Mud Loss	High	Intermittent circulation losses developed while drilling ahead. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2005-12-17 1900 m	Mud Loss	High	Flow-out dropped below flow-in with pit loss. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Track flow balance and pit volume trend before losses become severe.
2005-11-07 742 m	Mud Loss	Medium	Partial returns observed at shale shaker. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Track flow balance and pit volume trend before losses become severe.
2005-11-15 983 m	Mud Loss	Medium	Partial returns observed at shale shaker. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2005-12-04 1530 m	Kick	Medium	Flow-out exceeded flow-in and gas units increased. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2005-12-07 1611 m	Mud Loss	Medium	Active pit volume declined during stable pump rate. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.

Completion Summary

The synthetic well reached 2232 m MD in the Tipam interval. The NWIS knowledge record links 9 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.