

WELL COMPLETION REPORT (SYNTHETIC)

OIL-BGJ-008 - Baghjan-008

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000093
Field / District	Baghjan / Tinsukia
Block	OALP-IV-03
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2010-01-08 / 2010-04-25
Measured / TVD	2612 m / 2585 m
Trajectory	Vertical; inc 5.3 deg; az 12.7 deg
Formation Interval	1123-2074 m
Lithology	Fine-medium sandstone with shale interbeds
Pore Pressure Reference	2458 psi
Fracture Gradient	14.08 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Low (36.0/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	653	Surface
9 5/8 in casing	1514	Intermediate
7 in liner/casing	2298	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2010-03-04 1450 m	Stuck Pipe	Critical	Hookload became erratic during pipe movement. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Avoid prolonged static periods in high-drag interval.
2010-04-12 2318 m	Torque Spike	High	Rotary speed fluctuated during constant pump rate. Mitigation: Monitor torque derivative rather than absolute torque alone. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.
2010-02-20 1178 m	Torque Spike	Medium	Torque rose without corresponding pressure anomaly. Mitigation: Use staged parameter reduction to avoid torsional oscillation. Lesson: Use offset torque trend to set adaptive operating envelope.
2010-03-15 1693 m	Stuck Pipe	Medium	Hookload became erratic during pipe movement. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.
2010-04-07 2207 m	Kick	Medium	Pit gain and flow with pumps off were observed. Mitigation: Maintain trip margin and use conservative connection practices. Lesson: Escalate connection-gas trends before entering correlated pressure zone.
2010-04-10 2281 m	Pressure Spike	Medium	Short-duration high-pressure excursion was recorded. Mitigation: Check solids loading and BHA hydraulics before drilling ahead. Lesson: Rate-of-change in pressure is more informative than a fixed threshold.
2010-02-26 1321 m	Mud Loss	Low	Partial returns observed at shale shaker. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.

Completion Summary

The synthetic well reached 2612 m MD in the Tipam interval. The NWIS knowledge record links 11 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.