

WELL COMPLETION REPORT (SYNTHETIC)

OIL-CHR-007 - Charali-007

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000083
Field / District	Charali / Biswanath
Block	PEL-ASSAM-08
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2020-04-17 / 2020-06-18
Measured / TVD	2628 m / 2576 m
Trajectory	Directional; inc 18.4 deg; az 191.4 deg
Formation Interval	1267-1875 m
Lithology	Fluvial sandstone with clay streaks
Pore Pressure Reference	2313 psi
Fracture Gradient	14.95 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Moderate (47.9/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	657	Surface
9 5/8 in casing	1524	Intermediate
7 in liner/casing	2312	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2020-05-12 1200 m	Mud Loss	High	Flow-out dropped below flow-in with pit loss. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Track flow balance and pit volume trend before losses become severe.
2020-06-06 2181 m	Stuck Pipe	High	High drag was recorded while circulating remained possible. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.
2020-06-13 2443 m	Pressure Spike	High	Standpipe pressure increased rapidly at nearly stable flow. Mitigation: Condition hole and confirm pressure normalization. Lesson: Use depth-matched offset hydraulic baseline for early warning.
2020-04-26 502 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Track flow balance and pit volume trend before losses become severe.
2020-05-08 1021 m	Mud Loss	Medium	Partial returns observed at shale shaker. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2020-05-11 1141 m	Stuck Pipe	Medium	High drag was recorded while circulating remained possible. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Avoid prolonged static periods in high-drag interval.
2020-05-15 1299 m	NPT	Medium	Drilling parameters were stable but operations were suspended. Mitigation: Classify NPT cause consistently for offset-well learning. Lesson: Consistent NPT coding enables meaningful cross-well comparison.

Completion Summary

The synthetic well reached 2628 m MD in the Tipam interval. The NWIS knowledge record links 13 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.