

WELL COMPLETION REPORT (SYNTHETIC)

OIL-DGB-010 - Digboi-010

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000109
Field / District	Digboi / Tinsukia
Block	PEL-ASSAM-01
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2015-04-26 / 2015-08-22
Measured / TVD	2527 m / 2487 m
Trajectory	Directional; inc 32.4 deg; az 255.9 deg
Formation Interval	1156-1811 m
Lithology	Sandstone-siltstone sequence
Pore Pressure Reference	2367 psi
Fracture Gradient	14.89 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	Moderate (51.9/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	631	Surface
9 5/8 in casing	1465	Intermediate
7 in liner/casing	2223	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2015-06-05 978 m	Cementing Issue	Critical	Observed returns did not match calculated displacement. Mitigation: Review loss history before cementing equivalent interval. Lesson: Offset loss history should inform cementing hydraulics.
2015-05-19 620 m	Mud Loss	High	Active pit volume declined during stable pump rate. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2015-05-19 632 m	Torque Spike	High	Sharp torque excursion occurred with RPM instability. Mitigation: Ream and condition hole if torque remains elevated. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.
2015-06-13 1158 m	Cementing Issue	High	Cement density/returns trend indicated placement uncertainty. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Offset loss history should inform cementing hydraulics.
2015-06-14 1169 m	Cementing Issue	High	Observed returns did not match calculated displacement. Mitigation: Control displacement rate and reconcile pumped/returned volumes. Lesson: Volume imbalance is an important cement-placement warning.
2015-06-24 1368 m	Mud Loss	High	Partial returns observed at shale shaker. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Track flow balance and pit volume trend before losses become severe.
2015-08-09 2277 m	Stuck Pipe	High	Torque and drag increased while ROP declined. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.

Completion Summary

The synthetic well reached 2527 m MD in the Tipam interval. The NWIS knowledge record links 17 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.