

WELL COMPLETION REPORT (SYNTHETIC)

OIL-KMC-008 - Kumchai-008

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000096
Field / District	Kumchai / Tinsukia
Block	OALP-IV-04
Basin	Assam-Arakan
Formation	Girujan (GRJ)
Spud / Completion	2024-03-26 / 2024-07-24
Measured / TVD	2196 m / 2178 m
Trajectory	Directional; inc 39.2 deg; az 317.8 deg
Formation Interval	1264-1855 m
Lithology	Argillaceous sandstone and shale
Pore Pressure Reference	2368 psi
Fracture Gradient	14.48 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Moderate (45.2/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	549	Surface
9 5/8 in casing	1273	Intermediate
7 in liner/casing	1932	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2024-04-20 577 m	Stuck Pipe	High	Rotary movement deteriorated progressively. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2024-04-28 734 m	Stuck Pipe	High	Hookload became erratic during pipe movement. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Avoid prolonged static periods in high-drag interval.
2024-04-29 751 m	Mud Loss	High	Partial returns observed at shale shaker. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2024-05-10 937 m	Stuck Pipe	High	Hookload became erratic during pipe movement. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.
2024-06-11 1478 m	Stuck Pipe	High	Hookload became erratic during pipe movement. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Avoid prolonged static periods in high-drag interval.
2024-06-27 1750 m	Stuck Pipe	High	Hookload became erratic during pipe movement. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Avoid prolonged static periods in high-drag interval.
2024-05-04 828 m	Pressure Spike	Medium	Circulating pressure climbed without equivalent torque change. Mitigation: Check solids loading and BHA hydraulics before drilling ahead. Lesson: Rate-of-change in pressure is more informative than a fixed threshold.

Completion Summary

The synthetic well reached 2196 m MD in the Girujan interval. The NWIS knowledge record links 12 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.