

WELL COMPLETION REPORT (SYNTHETIC)

OIL-MRN-003 - Moran-003

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000027
Field / District	Moran / Dibrugarh
Block	PEL-ASSAM-03
Basin	Assam-Arakan
Formation	Barail (BAR)
Spud / Completion	2004-01-09 / 2004-07-04
Measured / TVD	2752 m / 2736 m
Trajectory	Directional; inc 30.9 deg; az 86.4 deg
Formation Interval	1270-2175 m
Lithology	Fine sandstone with carbonaceous shale
Pore Pressure Reference	2719 psi
Fracture Gradient	14.39 ppg
Mud System	Glycol-PHPA WBM
NWIS Well Risk	Critical (63.2/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	688	Surface
9 5/8 in casing	1596	Intermediate
7 in liner/casing	2421	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2004-02-04 538 m	Kick	Critical	Drilling break followed by positive flow check. Mitigation: Maintain trip margin and use conservative connection practices. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2004-02-03 529 m	Cementing Issue	High	Displacement pressure became unstable. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Plan conservative displacement rate in weak formations.
2004-02-16 736 m	Mud Loss	High	Intermittent circulation losses developed while drilling ahead. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2004-03-05 1002 m	Mud Loss	High	Flow-out dropped below flow-in with pit loss. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Track flow balance and pit volume trend before losses become severe.
2004-04-03 1444 m	Mud Loss	High	Intermittent circulation losses developed while drilling ahead. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2004-05-02 1858 m	Kick	High	Pit gain and flow with pumps off were observed. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2004-05-14 2027 m	NPT	High	No depth progress occurred during the recorded interval. Mitigation: Maintain critical spares for recurring equipment failures. Lesson: Consistent NPT coding enables meaningful cross-well comparison.

Completion Summary

The synthetic well reached 2752 m MD in the Barail interval. The NWIS knowledge record links 16 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.