

DAILY DRILLING REPORT (SYNTHETIC)

OIL-BGJ-005 - Baghjan-005

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Baghjan / Tipam
Report Timestamp	2005-12-29 18:00:00
Current Depth	2232.0 m
Mud System	Low-Solids WBM
Well Risk	Low (34.4/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
12-24 13:42	2090	2805	210	105	10.81	827/805	11.7	Normal
12-25 03:31	2106	2880	251	103	10.58	790/818	12.5	Normal
12-25 17:20	2122	2925	200	117	11.17	854/866	12.3	Normal
12-26 07:08	2138	2887	229	107	10.90	714/748	12.8	Normal
12-26 20:57	2153	2926	249	105	11.08	767/768	9.3	Normal
12-27 10:45	2169	2825	250	111	10.92	716/691	10.9	Normal
12-28 00:34	2185	2803	232	103	10.93	787/759	9.2	Normal
12-28 14:22	2201	2812	245	102	10.99	777/774	9.0	Normal
12-29 04:11	2216	2882	257	91	11.05	800/776	12.9	Normal
12-29 18:00	2232	2879	239	111	10.87	729/757	14.5	Normal

Operational Events / Lessons

Kick (Medium) at 1530 m: Kick at 1530 m in Tipam. Flow-out exceeded flow-in and gas units increased. Circulated influx under controlled conditions. Outcome: Well stabilized after controlled circulation. Gas 208 units; pit change +7.5 bbl; mud weight 10.51 ppg. Recommended action: Set flow-check trigger for unexplained pit gain

Mud Loss (Medium) at 1611 m: Mud Loss at 1611 m in Tipam. Active pit volume declined during stable pump rate. Prepared graded lost-circulation pill. Outcome: Interval drilled through with controlled losses. Flow balance: 702/597 LPM (in/out); pit change -10.5 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

Mud Loss (Medium) at 1804 m: Mud Loss at 1804 m in Tipam. Active pit volume declined during stable pump rate. Stopped drilling and performed flow check. Outcome: Interval drilled through with controlled losses. Flow balance: 775/672 LPM (in/out); pit change -4.7 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Mud Loss (High) at 1900 m: Mud Loss at 1900 m in Tipam. Flow-out dropped below flow-in with pit loss. Reduced pump rate and monitored active pits. Outcome: Interval drilled through with controlled losses. Flow balance: 745/595 LPM (in/out); pit change -11.0 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.