

DAILY DRILLING REPORT (SYNTHETIC)

OIL-DRK-006 - Dirok-006

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Dirok / Girujan
Report Timestamp	2008-01-06 18:00:00
Current Depth	2139.0 m
Mud System	Low-Solids WBM
Well Risk	Low (39.2/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
01-02 00:00	2053	2850	196	113	11.00	826/854	12.1	Normal
01-02 12:40	2062	2847	217	101	10.85	810/809	10.9	Normal
01-03 01:20	2072	2798	234	105	10.83	806/832	8.4	Normal
01-03 14:00	2082	3043	269	123	10.88	785/790	14.7	Normal
01-04 02:40	2091	2839	234	110	10.90	787/802	15.0	Normal
01-04 15:20	2101	2877	243	99	10.97	746/747	14.0	Normal
01-05 04:00	2110	2936	233	106	11.23	743/739	11.7	Normal
01-05 16:40	2120	2864	256	113	10.91	763/766	10.1	Normal
01-06 05:20	2129	2858	235	117	10.89	731/750	10.2	Normal
01-06 18:00	2139	2916	222	106	10.98	678/664	8.7	Normal

Operational Events / Lessons

Torque Spike (Medium) at 1488 m: Torque Spike at 1488 m in Girujan. Torque rose without corresponding pressure anomaly. Reduced WOB and RPM. Outcome: Drilling resumed at reduced mechanical loading. Torque 303 kNm, drag 11.6 t, ROP 11.3 m/h. Recommended action: Compare live torque derivative with offset-well baseline

Torque Spike (Critical) at 1596 m: Torque Spike at 1596 m in Girujan. Torque rose without corresponding pressure anomaly. Reamed short interval and circulated cuttings. Outcome: Drilling resumed at reduced mechanical loading. Torque 346 kNm, drag 13.9 t, ROP 11.3 m/h. Recommended action: Compare live torque derivative with offset-well baseline

Mud Loss (Medium) at 1831 m: Mud Loss at 1831 m in Girujan. Flow-out dropped below flow-in with pit loss. Prepared graded lost-circulation pill. Outcome: Circulation stabilized after treatment. Flow balance: 818/661 LPM (in/out); pit change -11.9 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Cementing Issue (Medium) at 1870 m: Cementing Issue at 1870 m in Girujan. Cement density/returns trend indicated placement uncertainty. Reduced displacement rate and monitored returns. Outcome: Returns improved after rate reduction. Cement returns 34% with density 14.14 ppg. Recommended action: Use pressure-volume reconciliation during displacement

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.