

DAILY DRILLING REPORT (SYNTHETIC)

OIL-DRK-010 - Dirok-010

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Dirok / Tipam
Report Timestamp	2018-01-31 18:00:00
Current Depth	2160.0 m
Mud System	Low-Solids WBM
Well Risk	Moderate (45.4/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
01-26 15:26	2085	2774	204	104	10.99	785/782	10.0	Normal
01-27 05:03	2093	2942	277	109	10.89	787/808	10.0	Normal
01-27 18:40	2102	2677	195	108	10.87	785/788	8.9	Normal
01-28 08:17	2110	2883	196	112	10.86	805/792	9.2	Normal
01-28 21:54	2118	3063	218	98	10.91	732/757	14.8	Normal
01-29 11:31	2127	2854	278	102	10.83	792/794	12.7	Normal
01-30 01:08	2135	2819	238	104	11.15	796/821	11.5	Normal
01-30 14:45	2143	2869	229	114	10.96	804/801	11.5	Normal
01-31 04:22	2152	2984	212	108	11.06	809/811	10.9	Normal
01-31 18:00	2160	2896	238	111	10.99	732/749	10.4	Normal

Operational Events / Lessons

Mud Loss (Critical) at 1552 m: Mud Loss at 1552 m in Tipam. Partial returns observed at shale shaker. Reduced ROP and conditioned the hole. Outcome: Interval drilled through with controlled losses. Flow balance: 683/521 LPM (in/out); pit change -14.6 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

Stuck Pipe (Medium) at 1570 m: Stuck Pipe at 1570 m in Tipam. Hookload became erratic during pipe movement. Stopped drilling and circulated bottoms-up. Outcome: BHA freed and hole conditioned before drilling resumed. Torque 250 kNm, drag 27.2 t, ROP 9.6 m/h. Recommended action: Plan preventive wiper trip near analogous interval

Mud Loss (Critical) at 1867 m: Mud Loss at 1867 m in Tipam. Active pit volume declined during stable pump rate. Reduced ROP and conditioned the hole. Outcome: Interval drilled through with controlled losses. Flow balance: 729/511 LPM (in/out); pit change -13.7 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

Torque Spike (Low) at 1985 m: Torque Spike at 1985 m in Tipam. Torque rose without corresponding pressure anomaly. Reamed short interval and circulated cuttings. Outcome: Spike cleared with no equipment damage. Torque 268 kNm, drag 17.0 t, ROP 13.9 m/h. Recommended action: Compare live torque derivative with offset-well baseline

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.