

DAILY DRILLING REPORT (SYNTHETIC)

OIL-HPJ-005 - Hapjan-005

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Hapjan / Barail
Report Timestamp	2000-01-08 18:00:00
Current Depth	3125.0 m
Mud System	PHPA Water-Based Mud
Well Risk	Moderate (53.8/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
01-04 05:37	3038	3514	293	95	11.68	807/825	11.4	Normal
01-04 17:40	3048	3604	237	100	11.81	799/807	12.6	Normal
01-05 05:42	3057	3527	258	102	11.93	790/811	11.3	Normal
01-05 17:45	3067	3521	282	108	11.77	778/779	11.5	Normal
01-06 05:47	3077	3508	296	116	11.79	771/777	13.4	Normal
01-06 17:50	3086	3558	276	118	11.82	717/710	12.0	Normal
01-07 05:52	3096	3686	306	96	11.90	741/704	11.6	Normal
01-07 17:55	3106	3527	309	107	11.70	733/736	8.2	Normal
01-08 05:57	3115	3713	250	118	11.79	806/811	8.3	Normal
01-08 18:00	3125	3601	325	104	11.83	732/727	11.1	Normal

Operational Events / Lessons

Mud Loss (Medium) at 2422 m: Mud Loss at 2422 m in Barail. Flow-out dropped below flow-in with pit loss. Prepared graded lost-circulation pill. Outcome: Full returns restored and drilling resumed. Flow balance: 776/654 LPM (in/out); pit change -11.9 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Mud Loss (Critical) at 2481 m: Mud Loss at 2481 m in Barail. Intermittent circulation losses developed while drilling ahead. Prepared graded lost-circulation pill. Outcome: Full returns restored and drilling resumed. Flow balance: 756/547 LPM (in/out); pit change -17.8 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Mud Loss (High) at 2638 m: Mud Loss at 2638 m in Barail. Flow-out dropped below flow-in with pit loss. Reduced pump rate and monitored active pits. Outcome: Circulation stabilized after treatment. Flow balance: 758/618 LPM (in/out); pit change -3.9 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Mud Loss (High) at 2766 m: Mud Loss at 2766 m in Barail. Active pit volume declined during stable pump rate. Reduced ROP and conditioned the hole. Outcome: Interval drilled through with controlled losses. Flow balance: 783/639 LPM (in/out); pit change -6.6 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.