

DAILY DRILLING REPORT (SYNTHETIC)

OIL-HPJ-011 - Hapjan-011

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Hapjan / Tipam
Report Timestamp	2019-02-25 18:00:00
Current Depth	2687.0 m
Mud System	Low-Solids WBM
Well Risk	Moderate (54.0/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
02-21 20:31	2505	3174	256	108	11.30	782/767	8.2	Normal
02-22 06:54	2525	3082	265	97	11.39	787/805	5.5	Normal
02-22 17:17	2546	3204	234	104	11.28	831/860	10.8	Normal
02-23 03:40	2566	3150	233	109	11.36	779/773	11.4	Normal
02-23 14:04	2586	3155	253	104	11.23	737/739	10.8	Normal
02-24 00:27	2606	3418	248	111	11.36	830/840	14.3	Normal
02-24 10:50	2626	3292	222	90	11.34	813/816	10.8	Normal
02-24 21:13	2647	3136	306	111	11.48	727/725	11.7	Normal
02-25 07:36	2667	3201	301	102	11.36	734/723	11.5	Normal
02-25 18:00	2687	3295	318	96	11.71	751/725	8.5	Normal

Operational Events / Lessons

Mud Loss (Medium) at 1910 m: Mud Loss at 1910 m in Tipam. Partial returns observed at shale shaker. Reduced ROP and conditioned the hole. Outcome: Loss rate reduced to acceptable level. Flow balance: 678/556 LPM (in/out); pit change -2.8 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

NPT (Low) at 1972 m: NPT at 1972 m in Tipam. Rotary and WOB remained at zero during downtime. Recorded downtime cause and maintenance action. Outcome: System returned to service within revised plan. Recommended action: Flag repeated downtime patterns before mobilization

NPT (Low) at 2055 m: NPT at 2055 m in Tipam. Drilling parameters were stable but operations were suspended. Performed checks before restarting operations. Outcome: Downtime closed with maintenance record. Recommended action: Track recurring NPT cause by rig and equipment family

Torque Spike (Low) at 2464 m: Torque Spike at 2464 m in Tipam. Sharp torque excursion occurred with RPM instability. Reduced WOB and RPM. Outcome: Torque returned to operating band after parameter change. Torque 319 kNm, drag 19.0 t, ROP 8.7 m/h. Recommended action: Compare live torque derivative with offset-well baseline

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.