

DAILY DRILLING REPORT (SYNTHETIC)

OIL-KMC-004 - Kumchai-004

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Kumchai / Barail
Report Timestamp	2019-05-20 18:00:00
Current Depth	2663.0 m
Mud System	PHPA Water-Based Mud
Well Risk	Moderate (54.5/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
05-15 07:42	2565	3264	269	105	11.10	840/814	12.0	Normal
05-15 22:11	2576	3218	228	107	11.44	728/781	8.8	Normal
05-16 12:39	2587	3273	236	116	11.51	756/743	9.8	Normal
05-17 03:08	2598	3189	268	100	11.25	721/686	11.7	Normal
05-17 17:36	2608	3505	256	107	11.40	737/770	12.9	Normal
05-18 08:05	2619	3374	319	108	11.34	783/790	12.8	Normal
05-18 22:34	2630	3274	235	108	11.28	731/738	12.0	Normal
05-19 13:02	2641	3140	297	109	11.43	760/759	13.5	Normal
05-20 03:31	2652	3284	272	119	11.56	817/759	9.4	Normal
05-20 18:00	2663	3161	226	108	11.45	782/775	8.9	Normal

Operational Events / Lessons

Mud Loss (High) at 2112 m: Mud Loss at 2112 m in Barail. Flow-out dropped below flow-in with pit loss. Stopped drilling and performed flow check. Outcome: Loss rate reduced to acceptable level. Flow balance: 635/477 LPM (in/out); pit change -4.3 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

Kick (Medium) at 2400 m: Kick at 2400 m in Barail. Pit gain and flow with pumps off were observed. Circulated influx under controlled conditions. Outcome: Well stabilized after controlled circulation. Gas 127 units; pit change +10.0 bbl; mud weight 11.10 ppg. Recommended action: Review mud-weight margin 50 m before correlated kick depth

Stuck Pipe (High) at 2433 m: Stuck Pipe at 2433 m in Barail. Hookload became erratic during pipe movement. Reduced WOB and increased hole-cleaning circulation. Outcome: Restriction cleared without fishing operation. Torque 324 kNm, drag 42.5 t, ROP 4.3 m/h. Recommended action: Trigger stuck-pipe warning on combined torque/drag/ROP deterioration

Pressure Spike (Medium) at 2488 m: Pressure Spike at 2488 m in Barail. Circulating pressure climbed without equivalent torque change. Conditioned hole before restoring flow rate. Outcome: Standpipe pressure normalized after circulation. SPP 3523 psi at flow-in 802 LPM. Recommended action: Reduce pump rate and verify circulation if pressure trend persists

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.