

DAILY DRILLING REPORT (SYNTHETIC)

OIL-LKW-007 - Lakwa-007

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Lakwa / Tipam
Report Timestamp	2001-11-23 18:00:00
Current Depth	2477.0 m
Mud System	PHPA Water-Based Mud
Well Risk	Moderate (55.1/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
11-19 20:31	2310	3250	234	106	11.14	816/823	10.4	Normal
11-20 06:54	2328	3131	223	114	11.42	752/757	10.7	Normal
11-20 17:17	2347	2917	260	107	11.00	740/740	11.7	Normal
11-21 03:40	2366	3055	264	109	11.07	839/802	11.2	Normal
11-21 14:04	2384	3198	248	100	11.22	751/736	11.9	Normal
11-22 00:27	2403	3138	269	110	11.16	725/757	10.1	Normal
11-22 10:50	2421	3041	281	119	11.17	777/761	5.1	Normal
11-22 21:13	2440	3220	220	112	11.33	759/749	10.7	Normal
11-23 07:36	2458	3136	246	109	10.98	769/765	11.0	Normal
11-23 18:00	2477	3190	260	105	11.20	757/731	15.1	Normal

Operational Events / Lessons

Kick (Critical) at 1705 m: Kick at 1705 m in Tipam. Pit gain and flow with pumps off were observed. Circulated influx under controlled conditions. Outcome: Well stabilized after controlled circulation. Gas 280 units; pit change +18.8 bbl; mud weight 10.55 ppg. Recommended action: Set flow-check trigger for unexplained pit gain

Mud Loss (Medium) at 1972 m: Mud Loss at 1972 m in Tipam. Intermittent circulation losses developed while drilling ahead. Prepared graded lost-circulation pill. Outcome: Full returns restored and drilling resumed. Flow balance: 794/674 LPM (in/out); pit change -4.6 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Kick (High) at 1991 m: Kick at 1991 m in Tipam. Pit gain and flow with pumps off were observed. Stopped drilling and performed flow check. Outcome: Influx circulated out and overbalance restored. Gas 187 units; pit change +15.8 bbl; mud weight 10.91 ppg. Recommended action: Review mud-weight margin 50 m before correlated kick depth

Mud Loss (Critical) at 2254 m: Mud Loss at 2254 m in Tipam. Active pit volume declined during stable pump rate. Prepared graded lost-circulation pill. Outcome: Interval drilled through with controlled losses. Flow balance: 795/649 LPM (in/out); pit change -10.6 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.