

DAILY DRILLING REPORT (SYNTHETIC)

OIL-LKW-012 - Lakwa-012

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Lakwa / Barail
Report Timestamp	2010-03-13 18:00:00
Current Depth	2531.0 m
Mud System	Low-Solids WBM
Well Risk	Moderate (47.6/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
03-08 09:55	2401	2596	247	102	11.27	863/832	6.8	Precursor
03-09 00:09	2415	3032	262	108	11.16	778/751	14.0	Precursor
03-09 14:23	2430	3255	271	118	11.36	871/831	8.6	Event
03-10 04:36	2444	3077	324	100	11.40	801/767	14.5	Recovery
03-10 18:50	2459	3209	235	105	11.43	718/737	15.9	Normal
03-11 09:04	2473	3192	229	107	11.20	779/767	14.2	Normal
03-11 23:18	2488	3038	280	120	11.42	753/765	12.7	Normal
03-12 13:32	2502	3193	258	116	11.24	798/804	14.2	Normal
03-13 03:46	2516	3245	258	115	11.04	810/812	13.8	Normal
03-13 18:00	2531	3151	269	116	11.27	787/830	11.6	Normal

Operational Events / Lessons

Mud Loss (Medium) at 1738 m: Mud Loss at 1738 m in Barail. Partial returns observed at shale shaker. Reduced ROP and conditioned the hole. Outcome: Interval drilled through with controlled losses. Flow balance: 728/636 LPM (in/out); pit change -1.1 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

Mud Loss (Low) at 2005 m: Mud Loss at 2005 m in Barail. Partial returns observed at shale shaker. Stopped drilling and performed flow check. Outcome: Interval drilled through with controlled losses. Flow balance: 743/693 LPM (in/out); pit change -1.6 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Mud Loss (Medium) at 2123 m: Mud Loss at 2123 m in Barail. Partial returns observed at shale shaker. Prepared graded lost-circulation pill. Outcome: Interval drilled through with controlled losses. Flow balance: 783/726 LPM (in/out); pit change -2.5 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Mud Loss (Medium) at 2430 m: Mud Loss at 2430 m in Barail. Flow-out dropped below flow-in with pit loss. Stopped drilling and performed flow check. Outcome: Interval drilled through with controlled losses. Flow balance: 871/831 LPM (in/out); pit change -5.1 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.