

WELL COMPLETION REPORT (SYNTHETIC)

OIL-BGJ-004 - Baghjan-004

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000045
Field / District	Baghjan / Tinsukia
Block	OALP-IV-03
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2009-12-05 / 2010-03-19
Measured / TVD	2403 m / 2376 m
Trajectory	Vertical; inc 1.3 deg; az 71.7 deg
Formation Interval	1094-1856 m
Lithology	Fluvial sandstone with clay streaks
Pore Pressure Reference	2306 psi
Fracture Gradient	14.96 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	Low (38.9/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	600	Surface
9 5/8 in casing	1393	Intermediate
7 in liner/casing	2114	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2010-01-07 888 m	Kick	Medium	Pit gain and flow with pumps off were observed. Mitigation: Maintain trip margin and use conservative connection practices. Lesson: Escalate connection-gas trends before entering correlated pressure zone.
2010-01-26 1302 m	Stuck Pipe	Medium	High drag was recorded while circulating remained possible. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Avoid prolonged static periods in high-drag interval.
2010-02-02 1467 m	Torque Spike	Medium	Torque rose without corresponding pressure anomaly. Mitigation: Reduce WOB/RPM and circulate before resuming normal parameters. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.
2010-02-28 2014 m	Kick	Medium	Drilling break followed by positive flow check. Mitigation: Shut in, verify influx and circulate using approved well-control procedure. Lesson: Maintain mud-weight window using offset pressure evidence.
2010-01-08 910 m	Torque Spike	Low	Sharp torque excursion occurred with RPM instability. Mitigation: Use staged parameter reduction to avoid torsional oscillation. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.
2010-01-28 1346 m	Kick	Low	Flow-out exceeded flow-in and gas units increased. Mitigation: Maintain trip margin and use conservative connection practices. Lesson: Maintain mud-weight window using offset pressure evidence.
2010-02-23 1908 m	Torque Spike	Low	Rotary speed fluctuated during constant pump rate. Mitigation: Ream and condition hole if torque remains elevated. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.

Completion Summary

The synthetic well reached 2403 m MD in the Tipam interval. The NWIS knowledge record links 9 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.