

WELL COMPLETION REPORT (SYNTHETIC)

OIL-BGJ-007 - Baghjan-007

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000081
Field / District	Baghjan / Tinsukia
Block	OALP-IV-03
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2014-03-30 / 2014-06-30
Measured / TVD	2585 m / 2556 m
Trajectory	Directional; inc 28.9 deg; az 303.2 deg
Formation Interval	1607-2235 m
Lithology	Sandstone-siltstone sequence
Pore Pressure Reference	2905 psi
Fracture Gradient	14.47 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	Moderate (46.2/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	646	Surface
9 5/8 in casing	1499	Intermediate
7 in liner/casing	2274	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2014-05-07 1184 m	Stuck Pipe	Critical	Torque and drag increased while ROP declined. Mitigation: Apply approved freeing procedure and avoid excessive overpull. Lesson: Avoid prolonged static periods in high-drag interval.
2014-05-21 1565 m	Pressure Spike	High	Standpipe pressure increased rapidly at nearly stable flow. Mitigation: Condition hole and confirm pressure normalization. Lesson: Rate-of-change in pressure is more informative than a fixed threshold.
2014-05-25 1676 m	Kick	High	Unexpected background gas rise preceded influx. Mitigation: Shut in, verify influx and circulate using approved well-control procedure. Lesson: Maintain mud-weight window using offset pressure evidence.
2014-06-09 2047 m	Kick	High	Drilling break followed by positive flow check. Mitigation: Increase mud weight within fracture-margin limits and monitor gas trend. Lesson: Maintain mud-weight window using offset pressure evidence.
2014-06-24 2438 m	Cementing Issue	High	Cement density/returns trend indicated placement uncertainty. Mitigation: Review loss history before cementing equivalent interval. Lesson: Volume imbalance is an important cement-placement warning.
2014-05-12 1312 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Track flow balance and pit volume trend before losses become severe.
2014-06-12 2115 m	Mud Loss	Medium	Partial returns observed at shale shaker. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.

Completion Summary

The synthetic well reached 2585 m MD in the Tipam interval. The NWIS knowledge record links 10 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.