

WELL COMPLETION REPORT (SYNTHETIC)

OIL-BRH-007 - Borholla-007

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000082
Field / District	Borholla / Jorhat
Block	PEL-ASSAM-07
Basin	Assam-Arakan
Formation	Lakadong+Therria (LKT)
Spud / Completion	2017-05-06 / 2017-07-07
Measured / TVD	3297 m / 3262 m
Trajectory	Directional; inc 28.2 deg; az 86.3 deg
Formation Interval	1732-2671 m
Lithology	Sandstone with carbonaceous interbeds
Pore Pressure Reference	3171 psi
Fracture Gradient	14.63 ppg
Mud System	PHPA Water-Based Mud
NWIS Well Risk	Moderate (54.1/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	824	Surface
9 5/8 in casing	1912	Intermediate
7 in liner/casing	2901	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2017-06-05 1714 m	NPT	High	ROP dropped to zero during equipment unavailability. Mitigation: Use preventive maintenance triggers from repeated downtime patterns. Lesson: Recurring equipment downtime should influence planning and spares.
2017-06-08 1872 m	Cementing Issue	High	Cement returns were below planned percentage. Mitigation: Verify cement placement using pressure and volume balance. Lesson: Plan conservative displacement rate in weak formations.
2017-06-17 2312 m	Torque Spike	High	High torque developed while WOB remained elevated. Mitigation: Ream and condition hole if torque remains elevated. Lesson: Torque-rate change is a useful precursor even when pressure is stable.
2017-05-19 846 m	Kick	Medium	Drilling break followed by positive flow check. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2017-05-20 902 m	Cementing Issue	Medium	Displacement pressure became unstable. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Volume imbalance is an important cement-placement warning.
2017-05-26 1206 m	Stuck Pipe	Medium	High drag was recorded while circulating remained possible. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Avoid prolonged static periods in high-drag interval.
2017-05-29 1395 m	Mud Loss	Medium	Active pit volume declined during stable pump rate. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.

Completion Summary

The synthetic well reached 3297 m MD in the Lakadong+Therria interval. The NWIS knowledge record links 15 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.