

WELL COMPLETION REPORT (SYNTHETIC)

OIL-CHR-011 - Charali-011

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000131
Field / District	Charali / Biswanath
Block	PEL-ASSAM-08
Basin	Assam-Arakan
Formation	Girujan (GRJ)
Spud / Completion	2011-12-22 / 2012-03-19
Measured / TVD	2121 m / 2069 m
Trajectory	Directional; inc 39.3 deg; az 122.1 deg
Formation Interval	1219-1784 m
Lithology	Silty shale with sandstone lenses
Pore Pressure Reference	2176 psi
Fracture Gradient	14.18 ppg
Mud System	PHPA Water-Based Mud
NWIS Well Risk	Low (40.7/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	530	Surface
9 5/8 in casing	1230	Intermediate
7 in liner/casing	1866	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2012-02-11 1305 m	Cementing Issue	Critical	Displacement pressure became unstable. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Plan conservative displacement rate in weak formations.
2012-01-06 473 m	NPT	High	No depth progress occurred during the recorded interval. Mitigation: Verify equipment health before resuming drilling. Lesson: Consistent NPT coding enables meaningful cross-well comparison.
2012-01-08 539 m	Cementing Issue	High	Cement returns were below planned percentage. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Offset loss history should inform cementing hydraulics.
2012-01-31 1060 m	Mud Loss	High	Flow-out dropped below flow-in with pit loss. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2012-02-10 1293 m	Stuck Pipe	High	Hookload became erratic during pipe movement. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.
2012-01-01 350 m	Mud Loss	Medium	Flow-out dropped below flow-in with pit loss. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2012-01-01 364 m	NPT	Medium	ROP dropped to zero during equipment unavailability. Mitigation: Use preventive maintenance triggers from repeated downtime patterns. Lesson: Consistent NPT coding enables meaningful cross-well comparison.

Completion Summary

The synthetic well reached 2121 m MD in the Girujan interval. The NWIS knowledge record links 14 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.