

WELL COMPLETION REPORT (SYNTHETIC)

OIL-DGB-006 - Digboi-006

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000061
Field / District	Digboi / Tinsukia
Block	PEL-ASSAM-01
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2002-06-15 / 2002-12-06
Measured / TVD	2248 m / 2223 m
Trajectory	Vertical; inc 1.3 deg; az 134.8 deg
Formation Interval	1050-1560 m
Lithology	Sandstone-siltstone sequence
Pore Pressure Reference	2052 psi
Fracture Gradient	15.10 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	Moderate (47.1/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	562	Surface
9 5/8 in casing	1303	Intermediate
7 in liner/casing	1978	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2002-07-15 514 m	Mud Loss	High	Flow-out dropped below flow-in with pit loss. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Track flow balance and pit volume trend before losses become severe.
2002-08-03 754 m	Mud Loss	High	Active pit volume declined during stable pump rate. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2002-09-07 1194 m	Cementing Issue	High	Cement density/returns trend indicated placement uncertainty. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Volume imbalance is an important cement-placement warning.
2002-09-24 1398 m	Pressure Spike	High	Short-duration high-pressure excursion was recorded. Mitigation: Reduce pump rate, verify restriction and restore circulation gradually. Lesson: Correlate pressure anomalies with flow before escalating risk.
2002-10-07 1543 m	Kick	High	Flow-out exceeded flow-in and gas units increased. Mitigation: Shut in, verify influx and circulate using approved well-control procedure. Lesson: Escalate connection-gas trends before entering correlated pressure zone.
2002-10-20 1701 m	Mud Loss	High	Intermittent circulation losses developed while drilling ahead. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2002-10-28 1790 m	Stuck Pipe	High	Hookload became erratic during pipe movement. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.

Completion Summary

The synthetic well reached 2248 m MD in the Tipam interval. The NWIS knowledge record links 16 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.