

WELL COMPLETION REPORT (SYNTHETIC)

OIL-DRK-007 - Dirok-007

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000080
Field / District	Dirok / Dibrugarh
Block	OALP-III-08
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2017-10-31 / 2018-01-31
Measured / TVD	2483 m / 2449 m
Trajectory	Directional; inc 18.4 deg; az 107.0 deg
Formation Interval	1238-2024 m
Lithology	Fluvial sandstone with clay streaks
Pore Pressure Reference	2366 psi
Fracture Gradient	15.12 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	High (57.5/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	620	Surface
9 5/8 in casing	1440	Intermediate
7 in liner/casing	2185	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2017-11-19 660 m	Pressure Spike	High	Pressure trend exceeded recent moving baseline. Mitigation: Use pressure trend thresholds referenced to depth and flow rate. Lesson: Correlate pressure anomalies with flow before escalating risk.
2017-12-12 1241 m	Kick	High	Flow-out exceeded flow-in and gas units increased. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Maintain mud-weight window using offset pressure evidence.
2017-12-29 1685 m	NPT	High	Rotary and WOB remained at zero during downtime. Mitigation: Maintain critical spares for recurring equipment failures. Lesson: Consistent NPT coding enables meaningful cross-well comparison.
2018-01-16 2106 m	Cementing Issue	High	Cement density/returns trend indicated placement uncertainty. Mitigation: Verify cement placement using pressure and volume balance. Lesson: Volume imbalance is an important cement-placement warning.
2018-01-17 2130 m	Kick	High	Unexpected background gas rise preceded influx. Mitigation: Increase mud weight within fracture-margin limits and monitor gas trend. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2018-01-27 2386 m	Kick	High	Unexpected background gas rise preceded influx. Mitigation: Shut in, verify influx and circulate using approved well-control procedure. Lesson: Maintain mud-weight window using offset pressure evidence.
2017-11-13 493 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.

Completion Summary

The synthetic well reached 2483 m MD in the Tipam interval. The NWIS knowledge record links 20 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.