

WELL COMPLETION REPORT (SYNTHETIC)

OIL-DRK-008 - Dirok-008

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000092
Field / District	Dirok / Dibrugarh
Block	OALP-III-08
Basin	Assam-Arakan
Formation	Girujan (GRJ)
Spud / Completion	2015-08-16 / 2015-11-09
Measured / TVD	2265 m / 2226 m
Trajectory	Vertical; inc 4.4 deg; az 158.4 deg
Formation Interval	1094-1922 m
Lithology	Argillaceous sandstone and shale
Pore Pressure Reference	2156 psi
Fracture Gradient	14.65 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Low (39.2/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	566	Surface
9 5/8 in casing	1313	Intermediate
7 in liner/casing	1993	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2015-09-09 766 m	Fishing Operation	Critical	Mechanical obstruction prevented normal drilling progression. Mitigation: Review BHA failure mode before resuming drilling. Lesson: Capture retrieval outcome as institutional knowledge.
2015-09-05 656 m	Stuck Pipe	High	Torque and drag increased while ROP declined. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.
2015-09-20 1050 m	Kick	High	Flow-out exceeded flow-in and gas units increased. Mitigation: Increase mud weight within fracture-margin limits and monitor gas trend. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2015-08-31 515 m	Cementing Issue	Medium	Cement returns were below planned percentage. Mitigation: Control displacement rate and reconcile pumped/returned volumes. Lesson: Offset loss history should inform cementing hydraulics.
2015-09-16 943 m	Torque Spike	Medium	Sharp torque excursion occurred with RPM instability. Mitigation: Use staged parameter reduction to avoid torsional oscillation. Lesson: Use offset torque trend to set adaptive operating envelope.
2015-09-28 1248 m	Mud Loss	Medium	Active pit volume declined during stable pump rate. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2015-10-13 1610 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.

Completion Summary

The synthetic well reached 2265 m MD in the Girujan interval. The NWIS knowledge record links 9 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.