

WELL COMPLETION REPORT (SYNTHETIC)

OIL-GLK-002 - Geleki-002

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000017
Field / District	Geleki / Charaideo
Block	PEL-ASSAM-05
Basin	Assam-Arakan
Formation	Kopili (KOP)
Spud / Completion	2013-05-30 / 2013-09-11
Measured / TVD	3230 m / 3189 m
Trajectory	Vertical; inc 4.4 deg; az 221.3 deg
Formation Interval	1414-2127 m
Lithology	Calcareous shale and siltstone
Pore Pressure Reference	3108 psi
Fracture Gradient	15.58 ppg
Mud System	Glycol-PHPA WBM
NWIS Well Risk	High (60.4/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	807	Surface
9 5/8 in casing	1873	Intermediate
7 in liner/casing	2842	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2013-06-27 1032 m	NPT	Critical	ROP dropped to zero during equipment unavailability. Mitigation: Maintain critical spares for recurring equipment failures. Lesson: Recurring equipment downtime should influence planning and spares.
2013-07-16 1590 m	Torque Spike	High	Sharp torque excursion occurred with RPM instability. Mitigation: Reduce WOB/RPM and circulate before resuming normal parameters. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.
2013-08-12 2379 m	Pressure Spike	High	Short-duration high-pressure excursion was recorded. Mitigation: Check solids loading and BHA hydraulics before drilling ahead. Lesson: Correlate pressure anomalies with flow before escalating risk.
2013-09-03 3006 m	Kick	High	Pit gain and flow with pumps off were observed. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Maintain mud-weight window using offset pressure evidence.
2013-06-28 1070 m	NPT	Medium	Drilling parameters were stable but operations were suspended. Mitigation: Use preventive maintenance triggers from repeated downtime patterns. Lesson: Separate geological risk from equipment-driven NPT in analytics.
2013-07-03 1220 m	Mud Loss	Medium	Partial returns observed at shale shaker. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2013-07-27 1916 m	Mud Loss	Medium	Active pit volume declined during stable pump rate. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.

Completion Summary

The synthetic well reached 3230 m MD in the Kopili interval. The NWIS knowledge record links 10 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.