

WELL COMPLETION REPORT (SYNTHETIC)

OIL-GLK-004 - Geleki-004

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000041
Field / District	Geleki / Charaideo
Block	PEL-ASSAM-05
Basin	Assam-Arakan
Formation	Barail (BAR)
Spud / Completion	2016-03-27 / 2016-05-22
Measured / TVD	2525 m / 2500 m
Trajectory	Vertical; inc 1.9 deg; az 338.2 deg
Formation Interval	1176-1950 m
Lithology	Interbedded sandstone and shale
Pore Pressure Reference	2488 psi
Fracture Gradient	15.15 ppg
Mud System	PHPA Water-Based Mud
NWIS Well Risk	Moderate (52.9/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	631	Surface
9 5/8 in casing	1464	Intermediate
7 in liner/casing	2222	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2016-04-17 1059 m	Stuck Pipe	Critical	High drag was recorded while circulating remained possible. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2016-04-22 1302 m	Cementing Issue	Critical	Displacement pressure became unstable. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Plan conservative displacement rate in weak formations.
2016-05-04 1796 m	Mud Loss	Critical	Flow-out dropped below flow-in with pit loss. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2016-05-05 1835 m	Mud Loss	High	Flow-out dropped below flow-in with pit loss. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2016-05-08 1971 m	Stuck Pipe	High	Hookload became erratic during pipe movement. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2016-04-01 376 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2016-04-10 747 m	Pressure Spike	Medium	Standpipe pressure increased rapidly at nearly stable flow. Mitigation: Reduce pump rate, verify restriction and restore circulation gradually. Lesson: Use depth-matched offset hydraulic baseline for early warning.

Completion Summary

The synthetic well reached 2525 m MD in the Barail interval. The NWIS knowledge record links 11 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.