

WELL COMPLETION REPORT (SYNTHETIC)

OIL-GLK-006 - Geleki-006

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000065
Field / District	Geleki / Charaideo
Block	PEL-ASSAM-05
Basin	Assam-Arakan
Formation	Girujan (GRJ)
Spud / Completion	2007-03-12 / 2007-08-13
Measured / TVD	2278 m / 2250 m
Trajectory	Vertical; inc 3.7 deg; az 196.9 deg
Formation Interval	1398-2202 m
Lithology	Claystone-sandstone alternation
Pore Pressure Reference	2813 psi
Fracture Gradient	14.72 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Low (41.6/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	569	Surface
9 5/8 in casing	1321	Intermediate
7 in liner/casing	2004	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2007-04-22 726 m	Torque Spike	High	Sharp torque excursion occurred with RPM instability. Mitigation: Monitor torque derivative rather than absolute torque alone. Lesson: Use offset torque trend to set adaptive operating envelope.
2007-05-27 1224 m	Kick	High	Pit gain and flow with pumps off were observed. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2007-05-29 1250 m	Stuck Pipe	High	Rotary movement deteriorated progressively. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.
2007-06-07 1380 m	Cementing Issue	High	Observed returns did not match calculated displacement. Mitigation: Verify cement placement using pressure and volume balance. Lesson: Offset loss history should inform cementing hydraulics.
2007-04-25 772 m	Cementing Issue	Medium	Displacement pressure became unstable. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Offset loss history should inform cementing hydraulics.
2007-05-04 898 m	Torque Spike	Medium	Rotary speed fluctuated during constant pump rate. Mitigation: Ream and condition hole if torque remains elevated. Lesson: Use offset torque trend to set adaptive operating envelope.
2007-05-09 969 m	Mud Loss	Medium	Active pit volume declined during stable pump rate. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.

Completion Summary

The synthetic well reached 2278 m MD in the Girujan interval. The NWIS knowledge record links 12 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.