

WELL COMPLETION REPORT (SYNTHETIC)

OIL-GLK-009 - Geleki-009

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000101
Field / District	Geleki / Charaideo
Block	PEL-ASSAM-05
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2004-11-21 / 2005-02-25
Measured / TVD	2211 m / 2171 m
Trajectory	Vertical; inc 5.1 deg; az 52.9 deg
Formation Interval	1177-1996 m
Lithology	Fine-medium sandstone with shale interbeds
Pore Pressure Reference	2512 psi
Fracture Gradient	14.44 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	Low (42.1/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	552	Surface
9 5/8 in casing	1282	Intermediate
7 in liner/casing	1945	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2004-12-10 555 m	Torque Spike	High	High torque developed while WOB remained elevated. Mitigation: Monitor torque derivative rather than absolute torque alone. Lesson: Use offset torque trend to set adaptive operating envelope.
2005-02-18 2068 m	Fishing Operation	High	BHA retrieval required specialized tools. Mitigation: Confirm fish geometry before selecting retrieval tool. Lesson: Maintain detailed BHA inventory for rapid recovery planning.
2004-12-08 517 m	Mud Loss	Medium	Active pit volume declined during stable pump rate. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2004-12-16 703 m	Stuck Pipe	Medium	Rotary movement deteriorated progressively. Mitigation: Apply approved freeing procedure and avoid excessive overpull. Lesson: Avoid prolonged static periods in high-drag interval.
2004-12-20 800 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2004-12-21 812 m	Torque Spike	Medium	Sharp torque excursion occurred with RPM instability. Mitigation: Monitor torque derivative rather than absolute torque alone. Lesson: Torque-rate change is a useful precursor even when pressure is stable.
2004-12-23 848 m	Cementing Issue	Medium	Observed returns did not match calculated displacement. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Plan conservative displacement rate in weak formations.

Completion Summary

The synthetic well reached 2211 m MD in the Tipam interval. The NWIS knowledge record links 14 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.