

WELL COMPLETION REPORT (SYNTHETIC)

OIL-GLK-010 - Geleki-010

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000113
Field / District	Geleki / Charaideo
Block	PEL-ASSAM-05
Basin	Assam-Arakan
Formation	Kopili (KOP)
Spud / Completion	2003-08-20 / 2003-11-03
Measured / TVD	3475 m / 3457 m
Trajectory	Directional; inc 22.7 deg; az 155.7 deg
Formation Interval	1865-2663 m
Lithology	Calcareous shale and siltstone
Pore Pressure Reference	3942 psi
Fracture Gradient	15.71 ppg
Mud System	Glycol-PHPA WBM
NWIS Well Risk	Moderate (48.6/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	868	Surface
9 5/8 in casing	2015	Intermediate
7 in liner/casing	3058	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2003-08-28 542 m	Stuck Pipe	High	High drag was recorded while circulating remained possible. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.
2003-09-19 1531 m	Pressure Spike	High	Pressure trend exceeded recent moving baseline. Mitigation: Condition hole and confirm pressure normalization. Lesson: Use depth-matched offset hydraulic baseline for early warning.
2003-08-30 627 m	NPT	Medium	Drilling parameters were stable but operations were suspended. Mitigation: Verify equipment health before resuming drilling. Lesson: Recurring equipment downtime should influence planning and spares.
2003-09-09 1088 m	Kick	Medium	Pit gain and flow with pumps off were observed. Mitigation: Maintain trip margin and use conservative connection practices. Lesson: Maintain mud-weight window using offset pressure evidence.
2003-09-10 1141 m	Mud Loss	Medium	Partial returns observed at shale shaker. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2003-09-17 1454 m	Pressure Spike	Medium	Circulating pressure climbed without equivalent torque change. Mitigation: Check solids loading and BHA hydraulics before drilling ahead. Lesson: Rate-of-change in pressure is more informative than a fixed threshold.
2003-09-20 1608 m	Mud Loss	Medium	Flow-out dropped below flow-in with pit loss. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Track flow balance and pit volume trend before losses become severe.

Completion Summary

The synthetic well reached 3475 m MD in the Kopili interval. The NWIS knowledge record links 11 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.