

WELL COMPLETION REPORT (SYNTHETIC)

OIL-KMC-007 - Kumchai-007

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000084
Field / District	Kumchai / Tinsukia
Block	OALP-IV-04
Basin	Assam-Arakan
Formation	Girujan (GRJ)
Spud / Completion	2013-04-04 / 2013-06-15
Measured / TVD	1886 m / 1853 m
Trajectory	Directional; inc 36.2 deg; az 130.7 deg
Formation Interval	1016-1611 m
Lithology	Claystone-sandstone alternation
Pore Pressure Reference	2066 psi
Fracture Gradient	14.44 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Low (32.0/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	75	Conductor
13 3/8 in casing	471	Surface
9 5/8 in casing	1093	Intermediate
7 in liner/casing	1659	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2013-05-27 1444 m	Mud Loss	High	Partial returns observed at shale shaker. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Track flow balance and pit volume trend before losses become severe.
2013-04-20 539 m	Torque Spike	Medium	Sharp torque excursion occurred with RPM instability. Mitigation: Ream and condition hole if torque remains elevated. Lesson: Torque-rate change is a useful precursor even when pressure is stable.
2013-04-29 774 m	Mud Loss	Medium	Partial returns observed at shale shaker. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
2013-05-14 1120 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Reduce ECD, treat losses with LCM and confirm stable returns. Lesson: Track flow balance and pit volume trend before losses become severe.
2013-05-29 1482 m	Stuck Pipe	Medium	Rotary movement deteriorated progressively. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2013-04-23 623 m	Mud Loss	Low	Intermittent circulation losses developed while drilling ahead. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
2013-04-30 801 m	Fishing Operation	Low	Normal pipe-recovery attempts were unsuccessful. Mitigation: Confirm fish geometry before selecting retrieval tool. Lesson: Maintain detailed BHA inventory for rapid recovery planning.

Completion Summary

The synthetic well reached 1886 m MD in the Girujan interval. The NWIS knowledge record links 9 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.