

WELL COMPLETION REPORT (SYNTHETIC)

OIL-KMC-012 - Kumchai-012

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000144
Field / District	Kumchai / Tinsukia
Block	OALP-IV-04
Basin	Assam-Arakan
Formation	Girujan (GRJ)
Spud / Completion	2002-02-15 / 2002-06-07
Measured / TVD	2404 m / 2369 m
Trajectory	Vertical; inc 6.0 deg; az 59.0 deg
Formation Interval	1334-2218 m
Lithology	Silty shale with sandstone lenses
Pore Pressure Reference	2701 psi
Fracture Gradient	14.57 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Low (41.6/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	601	Surface
9 5/8 in casing	1394	Intermediate
7 in liner/casing	2115	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2002-02-27 385 m	Kick	Critical	Flow-out exceeded flow-in and gas units increased. Mitigation: Increase mud weight within fracture-margin limits and monitor gas trend. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2002-03-15 723 m	Kick	High	Flow-out exceeded flow-in and gas units increased. Mitigation: Increase mud weight within fracture-margin limits and monitor gas trend. Lesson: Escalate connection-gas trends before entering correlated pressure zone.
2002-05-02 1713 m	Torque Spike	High	Sharp torque excursion occurred with RPM instability. Mitigation: Use staged parameter reduction to avoid torsional oscillation. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.
2002-05-08 1822 m	Torque Spike	High	Sharp torque excursion occurred with RPM instability. Mitigation: Use staged parameter reduction to avoid torsional oscillation. Lesson: Avoid simultaneous high WOB and high RPM in correlated interval.
2002-03-07 563 m	Stuck Pipe	Medium	Hookload became erratic during pipe movement. Mitigation: Condition mud and verify cuttings transport before connection. Lesson: Avoid prolonged static periods in high-drag interval.
2002-03-21 866 m	Cementing Issue	Medium	Observed returns did not match calculated displacement. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Volume imbalance is an important cement-placement warning.
2002-04-02 1108 m	NPT	Medium	Drilling parameters were stable but operations were suspended. Mitigation: Use preventive maintenance triggers from repeated downtime patterns. Lesson: Separate geological risk from equipment-driven NPT in analytics.

Completion Summary

The synthetic well reached 2404 m MD in the Girujan interval. The NWIS knowledge record links 13 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.