

WELL COMPLETION REPORT (SYNTHETIC)

OIL-MRN-001 - Moran-001

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000003
Field / District	Moran / Dibrugarh
Block	PEL-ASSAM-03
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2003-02-14 / 2003-05-13
Measured / TVD	2580 m / 2541 m
Trajectory	Directional; inc 15.2 deg; az 267.1 deg
Formation Interval	1250-1912 m
Lithology	Sandstone-siltstone sequence
Pore Pressure Reference	2337 psi
Fracture Gradient	14.77 ppg
Mud System	PHPA Water-Based Mud
NWIS Well Risk	Moderate (49.5/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	645	Surface
9 5/8 in casing	1496	Intermediate
7 in liner/casing	2270	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2003-03-30 1409 m	Fishing Operation	Critical	Normal pipe-recovery attempts were unsuccessful. Mitigation: Review BHA failure mode before resuming drilling. Lesson: Capture retrieval outcome as institutional knowledge.
2003-04-12 1752 m	Kick	Critical	Pit gain and flow with pumps off were observed. Mitigation: Re-establish overbalance and monitor pit/flow balance. Lesson: Treat pit gain plus gas increase as an early influx indicator.
2003-02-26 497 m	NPT	High	No depth progress occurred during the recorded interval. Mitigation: Maintain critical spares for recurring equipment failures. Lesson: Separate geological risk from equipment-driven NPT in analytics.
2003-03-23 1211 m	Stuck Pipe	High	Torque and drag increased while ROP declined. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2003-03-31 1424 m	Stuck Pipe	High	Rotary movement deteriorated progressively. Mitigation: Apply approved freeing procedure and avoid excessive overpull. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2003-04-09 1678 m	Pressure Spike	High	Circulating pressure climbed without equivalent torque change. Mitigation: Reduce pump rate, verify restriction and restore circulation gradually. Lesson: Rate-of-change in pressure is more informative than a fixed threshold.
2003-05-07 2408 m	Mud Loss	High	Intermittent circulation losses developed while drilling ahead. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.

Completion Summary

The synthetic well reached 2580 m MD in the Tipam interval. The NWIS knowledge record links 12 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.