

WELL COMPLETION REPORT (SYNTHETIC)

OIL-MRN-005 - Moran-005

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000051
Field / District	Moran / Dibrugarh
Block	PEL-ASSAM-03
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	1998-07-02 / 1998-12-14
Measured / TVD	2165 m / 2132 m
Trajectory	Vertical; inc 5.4 deg; az 215.6 deg
Formation Interval	1098-1719 m
Lithology	Fluvial sandstone with clay streaks
Pore Pressure Reference	2187 psi
Fracture Gradient	14.69 ppg
Mud System	Low-Solids WBM
NWIS Well Risk	Low (36.8/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	541	Surface
9 5/8 in casing	1255	Intermediate
7 in liner/casing	1905	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
1998-08-05 570 m	Mud Loss	Critical	Partial returns observed at shale shaker. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Track flow balance and pit volume trend before losses become severe.
1998-11-24 1926 m	Mud Loss	Critical	Intermittent circulation losses developed while drilling ahead. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Prepare LCM package before approaching correlated offset-well loss depth.
1998-09-05 960 m	Torque Spike	High	Sharp torque excursion occurred with RPM instability. Mitigation: Ream and condition hole if torque remains elevated. Lesson: Torque-rate change is a useful precursor even when pressure is stable.
1998-09-07 994 m	Mud Loss	High	Flow-out dropped below flow-in with pit loss. Mitigation: Spot graded LCM pill and circulate at reduced rate. Lesson: Track flow balance and pit volume trend before losses become severe.
1998-10-27 1600 m	Torque Spike	High	Sharp torque excursion occurred with RPM instability. Mitigation: Reduce WOB/RPM and circulate before resuming normal parameters. Lesson: Torque-rate change is a useful precursor even when pressure is stable.
1998-11-25 1939 m	NPT	High	ROP dropped to zero during equipment unavailability. Mitigation: Verify equipment health before resuming drilling. Lesson: Consistent NPT coding enables meaningful cross-well comparison.
1998-08-28 869 m	Stuck Pipe	Medium	High drag was recorded while circulating remained possible. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Avoid prolonged static periods in high-drag interval.

Completion Summary

The synthetic well reached 2165 m MD in the Tipam interval. The NWIS knowledge record links 15 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.