

WELL COMPLETION REPORT (SYNTHETIC)

OIL-MRN-013 - Moran-013

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000147
Field / District	Moran / Dibrugarh
Block	PEL-ASSAM-03
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	2008-07-08 / 2009-01-03
Measured / TVD	2411 m / 2369 m
Trajectory	Vertical; inc 3.7 deg; az 152.9 deg
Formation Interval	1391-2121 m
Lithology	Fine-medium sandstone with shale interbeds
Pore Pressure Reference	2797 psi
Fracture Gradient	14.69 ppg
Mud System	KCl Polymer WBM
NWIS Well Risk	Low (39.3/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	602	Surface
9 5/8 in casing	1398	Intermediate
7 in liner/casing	2121	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
2008-09-28 1220 m	Fishing Operation	Critical	Mechanical obstruction prevented normal drilling progression. Mitigation: Confirm fish geometry before selecting retrieval tool. Lesson: Maintain detailed BHA inventory for rapid recovery planning.
2008-10-02 1268 m	Stuck Pipe	Critical	Rotary movement deteriorated progressively. Mitigation: Improve hole cleaning, work pipe and back-ream within operating envelope. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2008-08-24 767 m	Pressure Spike	High	Short-duration high-pressure excursion was recorded. Mitigation: Condition hole and confirm pressure normalization. Lesson: Use depth-matched offset hydraulic baseline for early warning.
2008-08-31 851 m	Torque Spike	High	High torque developed while WOB remained elevated. Mitigation: Use staged parameter reduction to avoid torsional oscillation. Lesson: Torque-rate change is a useful precursor even when pressure is stable.
2008-09-26 1187 m	Stuck Pipe	High	Torque and drag increased while ROP declined. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Avoid prolonged static periods in high-drag interval.
2008-09-12 1008 m	Stuck Pipe	Medium	Rotary movement deteriorated progressively. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Use offset stuck-pipe depth to increase circulation and reaming frequency.
2008-10-03 1284 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Stage circulation and monitor pit volume before resuming drilling. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.

Completion Summary

The synthetic well reached 2411 m MD in the Tipam interval. The NWIS knowledge record links 13 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.