

WELL COMPLETION REPORT (SYNTHETIC)

OIL-RDS-005 - Rudrasagar-005

NWIS prototype document - not an Oil India Limited operational record

API Number	OIL-ASM-000054
Field / District	Rudrasagar / Sivasagar
Block	PEL-ASSAM-06
Basin	Assam-Arakan
Formation	Tipam (TIP)
Spud / Completion	1998-05-08 / 1998-09-18
Measured / TVD	2491 m / 2449 m
Trajectory	Vertical; inc 2.7 deg; az 267.4 deg
Formation Interval	1153-1747 m
Lithology	Fine-medium sandstone with shale interbeds
Pore Pressure Reference	2201 psi
Fracture Gradient	14.98 ppg
Mud System	PHPA Water-Based Mud
NWIS Well Risk	Moderate (49.1/100)

Casing Program

String	Set Depth (m)	Purpose
20 in conductor	80	Conductor
13 3/8 in casing	622	Surface
9 5/8 in casing	1444	Intermediate
7 in liner/casing	2192	Production

Significant Historical Events and Lessons

Date / Depth	Event	Severity	Evidence / mitigation / lesson
1998-06-29 1094 m	Kick	Critical	Drilling break followed by positive flow check. Mitigation: Maintain trip margin and use conservative connection practices. Lesson: Maintain mud-weight window using offset pressure evidence.
1998-06-04 630 m	NPT	High	Drilling parameters were stable but operations were suspended. Mitigation: Classify NPT cause consistently for offset-well learning. Lesson: Separate geological risk from equipment-driven NPT in analytics.
1998-06-21 945 m	Kick	High	Flow-out exceeded flow-in and gas units increased. Mitigation: Increase mud weight within fracture-margin limits and monitor gas trend. Lesson: Maintain mud-weight window using offset pressure evidence.
1998-07-03 1177 m	Mud Loss	High	Active pit volume declined during stable pump rate. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
1998-08-05 1752 m	Cementing Issue	High	Displacement pressure became unstable. Mitigation: Use staged cementing response when returns deteriorate. Lesson: Volume imbalance is an important cement-placement warning.
1998-05-24 432 m	Mud Loss	Medium	Intermittent circulation losses developed while drilling ahead. Mitigation: Optimize hydraulics and maintain conservative ROP through loss interval. Lesson: Use conservative hydraulics when re-entering equivalent loss-prone interval.
1998-06-12 784 m	Stuck Pipe	Medium	High drag was recorded while circulating remained possible. Mitigation: Reduce ROP and increase circulation before high-angle interval. Lesson: Rising torque plus falling ROP should trigger hole-cleaning action.

Completion Summary

The synthetic well reached 2491 m MD in the Tipam interval. The NWIS knowledge record links 13 historical operational events to depth-matched telemetry. Risk classification is derived from formation, depth, trajectory and event history rather than formation alone.

This report is generated solely for SIH/NWIS prototyping and model development.