Started on	Tuesday, 8 September 2026, 5:41 PM
State	Finished
Completed on	Tuesday, 8 September 2026, 5:59 PM
Time taken	17 mins 55 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int arr1[n];
    int arr2[n];
    for(int i=0;i<n;i++){
    scanf("%d",&arr1[i]);}
    for(int i=0;i<n;i++){
        scanf("%d",&arr2[i]);
    }
    for(int i=0;i<n-1;i++){
        for(int j=0;j<n-i-1;j++){
            if(arr1[j]>arr1[j+1]){
                int temp=arr1[j];
                arr1[j]=arr1[j+1];
                arr1[j+1]=temp;
            }
        }
    }
    for(int i=0;i<n-1;i++){
        for(int j=0;j<n-i-1;j++){
            if(arr2[j]<arr2[j+1]){
               int temp=arr2[j];
               arr2[j]=arr2[j+1];
               arr2[j+1]=temp;
            }
        }
    }
    int result=0;
    for(int i=0;i<n;i++){
        int answer=arr1[i]*arr2[i];
        result=result+answer;
    }
    printf("%d",result);
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.