Status	Finished
Started	Sunday, 11 October 2026, 9:20 AM
Completed	Sunday, 11 October 2026, 9:27 AM
Duration	6 mins 41 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

a. Elements of set2 will get appended to set1

b. Elements of set1 will get appended to set2

c. A new set will be created with the elements of both set1 and set2 ✓

d. A new set will be created with the unique elements of set1 and set2.

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True
False

b. False
True

c. True ✓
True

d. False
False

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (10, 20, 30, 40) (40, 50, 60, 70, 80)

b. (30, 40, 50)(40, 50, 60, 70, 80)

c. (30, 40, 50) (10, 20, 30, 40)

d. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, '10', 50, 20, 60, 30} ✓

b. {40, '10', 50, 20, 60, 30}

c. SynatxError: Different types cannot be used with sets

d. {40, 10, 50, 20, 60, 30}

Question **5**

Correct

Mark 1.00 out of 1.00

Select all the correct options to remove "ECE" from the set.

```
sampleSet = {"ECE", "R&A", "MCT"}
```

a. remove.sampleSet("ECE")

b. sampleSet.delete("ECE")

c. sampleSet.discard("ECE") ✓

d. del.sampleSet("ECE")

Question **6**

Correct

Mark 1.00 out of 1.00

Which of the following is a Python tuple?

a. (1,4,5,6,7) ✓

b. [1,2,3,4]

c. ("Wonder")

d. {1,3,8,9,41}

Question **7**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. i,ii ✓

b. ii

c. All of the above

d. iii

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

- a. (1,2,3,4,5,6) ✓
- b. (1,2,3)(4,5,6)
- c. Error
- d. (1,2,3,3,2,1)

Question **9**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (55, 44, 33, 22, 11)
x = [t1[i] for i in range(0, len(t1), 2)]
print(x)
```

- a. [55, 33, 11] ✓
- b. (55,33,11)
- c. ([55,33,11])
- d. [(55,33,11)]

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. False
True

c. True ✓
True

d. True
False

Question **11**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. (16,17,18,19) ✓

b. Error

c. (25,19,18,17)

d. (16,17,18)

Question **12**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓

Question **13**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. (1, 4, 8)

b. [1, 2, 4, 3, 8, 9]

c. [1, 4, 8] ✓

d. [2, 3, 9]

Question **14**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
print type(a)
```

a. <class 'str'> ✓

b. <class 'tuple'>

c. <class 'int'>

d. str

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {'rec', True, ('cse', 'ece')}

b. {'rec', 1, ('cse', 'ece'),True}

c. {'rec', 1, ('cse', 'ece')} ✓

d. Error