AMRITA SCHOOL OF COMPUTING, COIMBATORE

Department of Computer Science and Engineering

Coimbatore, Tamil Nadu, India — 641112

CAPSTONE PROJECT FINAL REPORT

WEATHER-DRIVEN FOOD ORDER PATTERNS:

Demand Forecasting, Menu Association Mining, and Decision Support for Restaurant Operations in Coimbatore

---

Course: 23CSE452 Business Analytics (Units 1, 2, and 3 Final Submission)

Programme: B.Tech in Computer Science and Engineering

Academic Year: 2026–2027 | **Submission Date:** November 2026

Submitted by: Project Group 9

Student Name	Register Number	Core Module Ownership
Sai Sri Satvic L	CB.SC.U4CSE23225	Preprocessing, Features & Market Basket Mining (P3)
Deepak S	CB.SC.U4CSE23267	Predictive Modeling & Model Selection (P5)
Swasthika P S	CB.SC.U4CSE23350	Exploratory Data Analysis & Streamlit Dashboard (P4)
Priyadharshini	CB.SC.U4CSE23438	Time-Series Forecasting (P1)
Aashiq Edavalapati	CB.SC.U4CSE23560	Menu Engineering & Transaction Generator (P2)

Under the Guidance of:

Ms. Rohini S

Assistant Professor, Department of Computer Science and Engineering

Amrita School of Computing, Amrita Vishwa Vidyapeetham

Declaration and Acknowledgement

We hereby declare that the capstone project entitled **"Weather-Driven Food Order Patterns: Demand Forecasting, Menu Association Mining, and Decision Support for Restaurant Operations in Coimbatore"** submitted for the course **23CSE452 Business Analytics** at Amrita School of Computing represents our own original and collaborative work. Every software component, statistical test, econometric model, machine learning architecture, rule mining engine, and interactive dashboard in this repository was constructed, debugged, and validated by our team members. Where external open-source packages, public APIs (such as Open-Meteo), or generative AI tools were consulted for syntactic assistance, code scaffolding, or formatting, their roles have been cataloged in Section 8.3.

We record our sincere gratitude to our course guide, **Mrs. Rohini S**, and the faculty of the Department of Computer Science and Engineering for their continuous technical scrutiny, milestone reviews, and rubric feedback across Units 1, 2, and 3. Their rigorous standards for empirical validation and practical business applicability kept our research focused on solving real-world operational challenges.

Sai Sri Satvic L (CB.SC.U4CSE23225)
Deepak S (CB.SC.U4CSE23267)
Swasthika P S (CB.SC.U4CSE23350)
Priyadharshini (CB.SC.U4CSE23438)
Aashiq Edavalapati (CB.SC.U4CSE23560)

Abstract

Operating a commercial restaurant kitchen in Coimbatore during monsoon seasons is an operational challenge governed by tropical weather variability. When sudden afternoon downpours strike, physical footfall vanishes while digital food delivery orders surge. Relying on static weekday averages triggers two severe failures: raw material stockouts during downpours and perishable food waste during clear afternoons. To solve these failures, we engineered an end-to-end business analytics decision-support pipeline combining 1,097 continuous days of physical meteorological observations from Open-Meteo (September 2023 to September 2026) with 182,696 granular delivery transactions across 80 items in Coimbatore, Tamil Nadu.

Our framework spans descriptive, predictive, and prescriptive analytics. Exploratory analysis (Unit 1) quantifies a +29.0% demand surge on heavy rain days ($\geq$ 15 mm) alongside a +25.5% weekend lift (r = +0.51). In Unit 2, eleven forecasting models were compared over a full year of past-only testing, and Ridge regression was selected: it matches the most accurate models (MAE = 15.08 orders/day, R^2 = 0.92) while being the simplest to interpret and deploy, and weather inputs cut its error by 60%. In Unit 3, we deploy two advanced engines: (1) SARIMAX time-series forecasting across 917 rolling walk-forward folds (MAE 15.75 orders/day, 59.6% error reduction), and (2) weather-segmented association rule mining (FP-Growth), which discovers rain-driven comfort food affinity spikes (Hot Masala Tea and Onion Pakora: Lift 3.42, Confidence 68.2%) alongside the collapse of cold dessert affinities. We package these engines into an interactive Streamlit application with a +25 order safety buffer. This operational intervention eliminates 80.2% of stockouts, cuts food prep waste by 34.1%, and generates an estimated net annual profit lift of INR 516,000.

Executive Summary

Commercial restaurant kitchens operate on thin margins (8%–15%), where profitability depends on ingredient turnover and prep pacing. In Coimbatore, the Southwest and Northeast monsoons create sharp demand shocks that static calendar planning cannot accommodate.

This capstone project replaces spreadsheet heuristics with an automated analytics engine. By linking meteorological telemetry with transaction patterns, we establish that weather is the primary exogenous driver of volume variability. Integrating weather regressors reduces the volume forecast error of the selected Ridge model from 37.4 to 15.1 orders per day. Furthermore, market basket mining demonstrates that rain alters not only aggregate volume but basket composition: demand shifts toward hot soups and fried snacks, while chilled beverages plummet. By implementing an optimized +25 order safety buffer on rain days, restaurants eliminate stockouts and reduce food waste, unlocking an estimated annual financial return of INR 516,000 on a single-store operational footprint.

Abbreviations and Acronyms

Acronym	Full Definition	Acronym	Full Definition
ADF	Augmented Dickey-Fuller Test	**MAE**	Mean Absolute Error
AIC	Akaike Information Criterion	**MAPE**	Mean Absolute Percentage Error
API	Application Programming Interface	**MASE**	Mean Absolute Scaled Error
ARM	Association Rule Mining	**NE**	Northeast Monsoon (Oct–Dec)
CV	Cross-Validation	**POS**	Point of Sale
DM	Diebold-Mariano Test	**RMSE**	Root Mean Squared Error
EDA	Exploratory Data Analysis	**SARIMAX**	Seasonal ARIMA with Exogenous Regressors
FP	Frequent Pattern (FP-Growth)	**SHAP**	Shapley Additive exPlanations
GLM	Generalized Linear Model	**STL**	Seasonal-Trend Decomposition using LOESS
IMD	India Meteorological Department	**SW**	Southwest Monsoon (Jun–Sep)
IQR	Interquartile Range	**VIF**	Variance Inflation Factor
KPI	Key Performance Indicator	**XGBoost**	Extreme Gradient Boosting

Contents

Declaration and Acknowledgement ii

Abstract ii

Executive Summary ii

Abbreviations and Acronyms iii

1 Introduction, Business Objectives and Literature Review 1
- 1.1 Context and Scope . . . 1
- 1.2 End-to-End Analytics Workflow . . . 1
- 1.3 Related Analytics Work and Research Gap . . . 1

2 Dataset Collection, Validation and Preparation 2
- 2.1 Provenance, Coverage and Challenges . . . 3
- 2.2 Data Quality, Privacy and Ethics . . . 4
- 2.3 Transformations and Usable Dataset . . . 4

3 Exploratory Data Analysis and Visualization (Unit 1) 4

4 Feature Engineering and Predictive Modelling (Unit 2) 6
- 4.1 Feature Construction and Leakage Audit . . . 6
- 4.2 Multicollinearity Diagnostics and Feature Selection . . . 6
- 4.3 Model Architectures and Held-Out Validation . . . 6
- 4.4 Model Interpretability and Subgroup Diagnostics . . . 7

5 Advanced Analytics (Unit 3): Two Selected Methods 8
- 5.1 Method 1: Time-Series Forecasting (SARIMAX and Prophet) . . . 8
- 5.2 Method 2: Weather-Segmented Association Rule Mining . . . 9

6 Comparative Analysis and Business Impact 10
- 6.1 Comparison of the Two Unit 3 Methods . . . 10
- 6.2 Comparison with Existing Studies and Similar Projects . . . 10

6.3 Model Selection over a Full Year and Weather Value (11 Models) 11
6.4 KPI-Based Business Impact, Operational Buffer and Scenarios 13

7 Interactive Application, Figure Index and Reproducibility 13
7.1 Mandatory Interactive Streamlit Dashboard 13
7.2 Figure Index and Reproduction Map 13
7.3 Code, Environment, and Reproducibility 13

8 End-to-End Validation, Traceability and Contributions 14
8.1 Completion, Validity and Risk Mitigation 14
8.2 Project Tracking and Individual Contributions 15
8.3 AI Use and Originality Declarations 15

9 Conclusion, Recommendations and Roadmap 15
9.1 Summary of Findings and Completed Scope 16
9.2 Actionable Recommendations for Restaurant Operators 16
9.3 Strategic Roadmap for Future Enhancements 16

References 17

A Extended Data Dictionary & Automated Validation Test Suite 18
A.1 Complete Menu Catalog (80 Items across 10 Families) 18
A.2 Automated Validation Test Harness Output 18

B Supplementary Model Diagnostics & Backtest Tables 19
B.1 Segment-Specific Forecast Error Breakdown 19
B.2 Complete Test Suite Execution (159 Tests) 19

C Dashboard User Guide & Installation Manual 19
C.1 Architecture and User Interface Layout 19
C.2 Step-by-Step Installation Guide 19

D Task Tracking Board & Verifiable Contribution Records 20

List of Figures

1 End-to-End Business Analytics Architecture across Units 1, 2, 3, and Streamlit Deployment. 2
2 Three-Year Daily Food Order Series . . . 5
3 Order Distribution across Weekdays and Rainfall Regimes . . . 5
4 Additive Seasonal-Trend Decomposition (STL) . . . 5
5 Pearson Correlation Heatmap . . . 6
6 Hold-Out Validation Performance for Unit 2 Supervised Models . . . 7
7 Model Interpretability and Explanations for Unit 2 Supervised Models . . . 7
8 Time-Series Backtest Diagnostics for Method 1 (`src/forecast.py`). . . . 8
9 Forecast Error (MAE) across Rainy vs Dry Regimes . . . 9
10 Weather-Segmented Association Rule Mining Diagnostics (`src/arm.py`). . . . 10
11 MAE With and Without Weather Inputs per Model . . . 12

List of Tables

1 Business Objectives to Technical KPI Mapping Matrix . . . 2
2 Literature Review and Research Gap Comparison . . . 3
3 Representative 5-Day Sample of Curated Dataset . . . 3
4 Data Transformations and Processing Pipeline Summary . . . 4
5 Field-to-Method Variable Mapping & Data Dictionary . . . 4
6 Supervised Models on the 56-Day Held-Out Test . . . 7
7 Time-Series Forecasting Walk-Forward Evaluation (917 Rolling Folds) vs Static Hold-Out 8
8 Top Weather-Segmented Association Rules (Rainy vs Dry Days) . . . 9
9 Comparison with Existing Studies and Industrial Baselines . . . 11
10 Model Comparison over 365 Test Days . . . 12
11 Error With and Without Weather, 365 Test Days . . . 12
12 Financial ROI and Operational Waste Reduction Projections . . . 13
13 Figure Index and Source Script Reproduction Map . . . 14
14 Objective-to-Evidence Traceability Matrix . . . 15
15 Individual Contribution and Task Ownership Matrix . . . 15
16 Actionable Operational Recommendations for Restaurant Management . . . 16
17 Model MAE across Environmental Segments . . . 19
18 Complete Capstone Task Execution and Commit Log . . . 20

1. Introduction, Business Objectives and Literature Review

1.1 Context and Scope

Profit margins in commercial food service hover between 8% and 15%. Operators face short-shelf-life perishables, strict prep cycles, and customer footfall that swings wildly across days and seasons. In South Indian urban hubs like Coimbatore, Tamil Nadu, tropical weather injects extreme friction into everyday kitchen planning. Nestled in the rain shadow of the Western Ghats at $\sim$ 411 meters elevation, Coimbatore endures a complex bimodal monsoon climate. The Southwest Monsoon (June–September) and the Northeast Monsoon (October–December) bring intense convective cloudbursts, interspersed with pre-monsoon heat spells exceeding 38°C in April and May.

When heavy afternoon rains hit, people avoid driving to restaurants; physical dine-in footfall plummets, but online delivery tickets surge on platforms like Swiggy and Zomato. On hot dry days, the reverse happens: customers skip heavy gravies and crave cold beverages. Despite these signals, head chefs and purchasing managers still rely on static calendar habits—preparing the same volume of rice, dough, and fillings every single Wednesday. That mismatch triggers two costly operational failures:

1. **Under-preparation on Rainy Days:** The kitchen exhausts key ingredients early in the rush. Line cooks face stockouts, delivery platforms cancel orders, delivery drivers wait in long queues, and frustrated customers switch to competitors.
2. **Over-preparation on Slow Days:** Perishable batters, doughs, and par-cooked proteins sit unsold, spoil overnight, and end up discarded, eroding operating margins.

To break this cycle, our capstone project constructs, evaluates, and deploys an automated decision-support pipeline that ingests atmospheric telemetry and forecasts to solve two operational challenges: predicting aggregate order volume and identifying weather-driven item co-occurrence. We structured our research around four practical engineering questions:

- **RQ1:** How much forecasting accuracy do physical meteorological signals (precipitation, temperature, humidity, wind) add over conventional calendar and autoregressive baselines?
- **RQ2:** Which supervised and time-series model families (regularized linear models, tree ensembles, SARIMAX, Prophet) deliver the lowest error and highest stability during sudden weather shocks?
- **RQ3:** How dramatically does inclement weather alter product co-occurrence in consumer baskets, and can those shifts be turned into high-margin menu combos?
- **RQ4:** How can these predictive models and association rules be packaged into an intuitive decision application that non-technical kitchen staff can run before the morning prep shift?

Table 1 maps each business objective to quantitative performance metrics, baseline benchmarks, and target criteria across the project.

1.2 End-to-End Analytics Workflow

The overall workflow connecting data ingestion, supervised modeling, advanced analytics, and operational deployment is illustrated in Figure 1.

1.3 Related Analytics Work and Research Gap

Demand forecasting in the hospitality and quick-service sector has evolved from classical Holt-Winters exponential smoothing to modern machine learning architectures. Taylor [14] demonstrated that supermarket demand exhibits dual-period seasonal patterns. However, classical models assume stationary variance and fail when external environmental shocks occur. Chen et al. [5] applied tree

Table 1: Business Objectives to Technical KPI Mapping Matrix

Core Business Objective	KPI & Unit	Baseline Benchmark	Target / Success Threshold	Analytical Module
Improve Daily Demand Forecast Accuracy	Mean Absolute Error (MAE) in orders/day	Baseline: 39.0 orders/day (Naive Weekday Persistence)	Target: < 16.0 orders/day (SARIMAX / Ridge)	Unit 2 & Unit 3 (Method 1)
Mitigate Kitchen Stockouts during Rain Surges	Stockout Incidence Probability (%)	Baseline: 18.2% on rainy days	Target: < 5.0% using +25 safety buffer	Unit 3 (Time-Series)
Curtail Perishable Food Preparation Waste	Waste Ratio (% of daily food prepared)	Baseline: 14.5% daily food waste	Target: < 9.5% (a 34% relative reduction)	Unit 2 & Unit 3
Optimize Wet-Weather Cross-Selling & Bundles	Average Basket Value (INR) & Lift Ratio	Baseline: Mean Lift 1.0; Basket INR 182	Target: Lift > 2.5 on comfort pairs; Basket +12%	Unit 3 (Method 2: ARM)
Deliver Operational Decision-Support Tool	System Usability & Response Latency (s)	Baseline: Manual spreadsheet lookup	Target: Interactive Streamlit UI < 1.5s latency	Streamlit Application




Figure 1: End-to-End Business Analytics Architecture across Units 1, 2, 3, and Streamlit Deployment.

ensembles to Chinese food delivery platforms, proving that rain increases ticket volumes; however, their study relied on static 80/20 splits and neglected item co-occurrence.

In parallel, market basket analysis pioneered by Agrawal et al. [1] has been widely deployed in retail. However, traditional association rule mining aggregates transactions over years into a static rule catalog, completely ignoring environmental context. A customer ordering ice cream on a sunny 36°C afternoon has a vastly different affinity vector than one ordering during an evening downpour. Table 2 benchmarks our capstone against prior research, highlighting our contribution in joint time-series and weather-segmented association mining.

2. Dataset Collection, Validation and Preparation

Table 2: Literature Review and Research Gap Comparison

Dimension	Chen et al. (2021) [5]	Taylor (2010) [14]	Our Capstone Architecture
Setting & Domain	Online food delivery in Tier-1 Chinese megacities.	Supermarket hourly customer footfall in the UK.	Single-store restaurant delivery & dining in Coimbatore, India.
Weather Regressors	Binary precipitation indicator only.	None (purely univariate calendar series).	Continuous rain depth, temp, humidity, wind, and non-linear interactions.
Validation Protocol	Static 80/20 train/test split (susceptible to leakage).	Univariate roll-forward evaluation.	917-fold walk-forward cross-validation + 56-day held-out test.
Market Basket Mining	Absent (volume aggregate only).	Absent.	Contextual weather-segmented ARM (Rainy vs Dry baskets).
Operational Output	Theoretical econometric parameters.	Offline research paper forecasts.	Interactive Streamlit UI with +25 safety buffer and combo engine.

2.1 Provenance, Coverage and Challenges

To avoid canned academic datasets from Kaggle or UCI, our architecture fuses authentic physical meteorological telemetry with granular restaurant transactions calibrated to Coimbatore's dining ecosystem:

1. **Meteorological Observations:** Daily and hourly records were queried from the Open-Meteo Historical Weather API [12] for Coimbatore (11.00°N, 76.99°E, elevation 411 m ASL), spanning 1,097 continuous days from September 24, 2023 to September 24, 2026. Retrieved regressors include precipitation depth (mm), maximum/minimum/mean ambient temperatures (°C), relative humidity (%), surface wind gusts (km/h), daylight duration, and WMO weather codes.
2. **Granular Order Transactions:** Because Indian MSME restaurant POS records are proprietary, we constructed an evidence-based demand generator (`src/generator.py`, random seed 42, documented in `docs/generator.md`). The generator is calibrated against three real-world benchmarks: (a) Swiggy's published South Indian dining reports [13], (b) historical rainfall distributions from the IMD Coimbatore Station [10], and (c) an empirical 27-person resident survey on dining preferences.

The catalog comprises **80 unique menu items** categorized across **10 culinary families**: *Egg, Starters & Gravies, Breads & Tiffin, Soups, Biryani & Rice, Chinese, Meals, Hot Beverages, Snacks, and Cold Drinks & Desserts*. Across the 1,097 days, the dataset contains **182,696 individual orders** with zero missing timestamps. Table 3 displays a representative 5-day processed sample.

Table 3: Representative 5-Day Sample of Curated Dataset (`data/raw/daily_orders.csv`)

Date	Orders	Temp Max (°C)	Precip (mm)	Humidity (%)	Wind (km/h)	Weekend	Rainy	Regime
2023-09-24	158	31.2	8.2	80.1	20.1	True	True	rainy
2023-09-25	147	30.0	2.8	82.2	17.4	False	True	rainy
2023-09-26	159	30.5	6.7	82.7	21.3	False	True	rainy
2023-09-27	162	30.8	9.6	82.1	23.7	False	True	rainy
2023-09-28	120	29.9	1.9	83.0	27.3	False	False	normal

True descriptive statistics for daily order volumes across the 1,097-day series are:

- **Mean:** 166.54 orders/day | **Standard Deviation:** 69.04 orders/day
- **Median:** 139.00 orders/day | **Interquartile Range (IQR):** 122.00 orders/day
- **Min–Max Range:** 73 to 354 orders/day
- **Weekend Mean (Fri–Sun):** 223.64 orders/day | **Weekday Mean (Mon–Thu):** 123.90 orders/day

2.2 Data Quality, Privacy and Ethics

The raw telemetry was screened for sensor dropouts, negative precipitation values, and duplicate records. Zero null values exist across the entire 1,097-day series. Outlier screening confirmed that peak volume spikes (> 300 orders) coincide exactly with torrential monsoon cloudbursts (> 25 mm) combined with weekend evenings, representing legitimate demand surges rather than data errors.

Bias Audit & Mitigations: We examined three potential biases: (a) *Collection Bias:* Weather measurements at Coimbatore airport station were matched with local elevation profiles to ensure hyper-local fidelity; (b) *Representation Bias:* POS basket patterns were checked across all 10 menu categories to prevent fast-food staples from eclipsing traditional meals; (c) *Measurement Bias:* Order timestamps were recorded in Indian Standard Time (IST) to avoid UTC boundary shifts. All customer identifiers were stripped at the transaction generator boundary, ensuring zero Personally Identifiable Information (PII) is processed.

2.3 Transformations and Usable Dataset

Data preparation applied strict chronological ordering. Feature transformations (lags, rolling averages) were computed using backward-looking windows only (`.shift(1)`) to eliminate data leakage. Table 4 details the transformation counts, and Table 5 provides the complete field mapping dictionary.

Table 4: Data Transformations and Processing Pipeline Summary

Pipeline Stage	Input Records	Output Records	Features	Transformation Operations Performed
Raw Weather Telemetry	1,097	1,097	11	API verification, timezone conversion (IST), range clipping.
Raw Transaction Stream	182,696	182,696	6	Tokenization of basket items, aggregation to daily order sums.
Feature Construction	1,097	1,090	25	Dropped first 7 days due to 7-day lag/rolling windows (`.shift(1)`).
Collinearity Reduction	1,090	1,090	16	Dropped `humidity_mean_pct` and `rain_mm` (VIF > 10 →< 4.0).
Hold-Out Test Partition	1,090	56 (Test)	16	Chronological freeze: Last 56 days held out for model evaluation.

Table 5: Field-to-Method Variable Mapping & Data Dictionary

Variable Name	Data Type	Origin / Derivation Description	Used in Unit / Method
`date`	Date	Calendar date index (YYYY-MM-DD)	Units 1, 2, 3 (All)
`order_count`	Integer	Daily total orders placed (Target Variable)	Units 1, 2, 3
`temp_max_c`	Float (°C)	Daily maximum ambient surface temperature	Unit 2, Unit 3 (Method 1)
`precip_mm`	Float (mm)	Total daily liquid precipitation depth	Units 1, 2, 3
`is_rainy`	Binary	1 if `precip_mm` ≥ 5.0 mm, else 0	Units 1, 2, 3
`heavy_rain`	Binary	1 if `precip_mm` ≥ 15.0 mm, else 0	Units 1, 2, 3
`is_fri_sun`	Binary	1 if day ∈ {Friday, Saturday, Sunday}, else 0	Units 1, 2, 3
`orders_lag1`	Float	Order volume from previous day ($t-1$)	Unit 2 (Supervised)
`orders_lag7`	Float	Order volume from same day previous week ($t-7$)	Unit 2 (Supervised)
`orders_roll7`	Float	7-day backward rolling mean order volume	Unit 2 (Supervised)
`rain_x_weekend`	Float	Interaction term: `is_rainy` × `is_fri_sun`	Unit 2, Unit 3
`items`	String	Semicolon-delimited list of basket items	Unit 3 (Method 2: ARM)

3. Exploratory Data Analysis and Visualization (Unit 1)

Exploratory Data Analysis was performed in `notebooks/04_eda.ipynb` and modularized in `src/eda.py`. The 1,097-day timeline reveals strong multi-scale seasonality governed by calendar rhythms and monsoon cycles.




Figure 2: Three-Year Daily Food Order Series (September 2023 – September 2026). Trajectory across 1,097 days displaying recurring annual monsoon peaks and weekend pulses [Python / Matplotlib, `notebooks/04_eda.ipynb`].

Figure 2 shows the complete three-year series. Order volumes exhibit sharp spikes during the Southwest (June–September) and Northeast (October–December) monsoons. Stationarity was assessed using the Augmented Dickey-Fuller (ADF) test: the test statistic ($t = -6.42$, $p < 0.0001$) strongly rejects the null hypothesis of a unit root, establishing that the series is stationary around a weekly cyclical mean.




Figure 3: Order Distribution across Weekdays and Rainfall Regimes. Boxplots illustrating weekend volume expansion and heavy rainfall surges (≥ 15 mm) [Python / Seaborn, `notebooks/04_eda.ipynb`].

Figure 3 decouples the calendar and weather drivers:

1. **Calendar Weekend Lift:** Friday through Sunday demand averages 223.64 orders/day, compared to 123.90 on weekdays—an underlying +80.5% increase driven by dining leisure habits.
2. **Precipitation Surge:** On heavy rain days (≥ 15 mm), volume expands to 228.0 orders/day, representing a +29.0% boost over baseline. When heavy rainfall coincides with a weekend, daily demand regularly exceeds 280 orders, exposing the kitchen to severe stockout risk under static planning.




Figure 4: Additive Seasonal-Trend Decomposition (STL) procedure by Cleveland et al. [6]. Isolating underlying trend, 7-day cyclical seasonality, and weather-driven residual shocks [Python / Statsmodels, `notebooks/04_eda.ipynb`].

The additive STL decomposition ($Y_t = T_t + S_t + R_t$) shown in Figure 4 extracts a rigid 7-day seasonal oscillation (S_t) that peaks on Saturday (+24.2 orders) and troughs on Tuesday (−18.6 orders). Crucially, the residual series (R_t) is not Gaussian white noise; its variance expands during monsoon months, demonstrating that weather injects exogenous shocks that univariate calendar models cannot resolve.

Figure 5 maps linear relationships across predictors. The single strongest linear driver is `is_fri_sun`




Figure 5: Pearson Correlation Heatmap across Meteorological Features and Temporal Lags. Demonstrating strong positive associations for `is_fri_sun` (r = +0.51) and `is_rainy` (r = +0.35) [Python / Seaborn, `notebooks/04_eda.ipynb`].

(r = +0.51), followed by `orders_roll7` (r = +0.48), `is_rainy` (r = +0.35), `precip_mm` (r = +0.29), and `orders_lag7` (r = +0.29). Maximum temperature shows near-zero linear correlation (r = −0.03), operating as a non-linear threshold suppressive only during extreme heat (> 34°C).

4. Feature Engineering and Predictive Modelling (Unit 2)

4.1 Feature Construction and Leakage Audit

Supervised predictive modeling was implemented in `src/features.py` and `src/predict.py`. A strict leakage audit ensured that no contemporaneous or future order counts leak into predictors:

- **Autoregressive Lags:** `orders_lag1` through `orders_lag7` were computed with backward shifts (`.shift(1)`).
- **Rolling Statistics:** 7-day and 14-day rolling means and standard deviations exclude day t.
- **Exogenous Weather Regressors:** Weather features represent same-day forecast values available at 06:00 AM.
- **Interaction Terms:** We engineered `rain_x_weekend` to capture the compounding multiplier of rain occurring during peak dining windows.

4.2 Multicollinearity Diagnostics and Feature Selection

Variance Inflation Factors (VIF) were computed to identify collinearity. Initial diagnostics flagged severe multicollinearity between `precip_mm` and `humidity_mean_pct` (VIF > 12.0). Removing `humidity_mean_pct` and `rain_mm` reduced all remaining feature VIF values below 3.8, ensuring stable coefficient estimation in regularized linear models.

4.3 Model Architectures and Held-Out Validation

We first trained three supervised models on all days before the final 56 and tested them on those 56 days in time order (31 Jul to 24 Sep 2026):


1. **Ridge Regression** (L2 regularisation [15]) with standard scaling.
2. **Random Forest** [3].
3. **XGBoost** [4].

Hyper-parameters were tuned only on the training window with a 5-fold `TimeSeriesSplit`. Nothing was shuffled. Table 6 compares the models with the seasonal-naive baseline (the same weekday one week earlier).


All three weather-aware models cut the baseline error by about three-quarters, from 58 to under 15 orders/day. The baseline repeats last week's calendar pattern, so it misses every day on which the

Table 6: Supervised Models on the 56-Day Held-Out Test (`results/model_metrics_overall.csv`)

Model	R^2	MAE	MSE	RMSE	MAPE (%)	Bias
Seasonal Naive Baseline	−0.56	58.21	5095.75	71.38	36.11	+0.50
Ridge Regression	**0.89**	**14.88**	**344.21**	**18.55**	**8.69**	+3.05
Random Forest	0.90	14.62	333.79	18.27	8.62	+1.80
XGBoost	0.90	14.73	329.13	18.14	8.81	+2.88



(a) Comparative Error Metrics on Hold-Out.




(b) Actual vs Predicted Orders (56 Days).

Figure 6: Hold-Out Validation Performance for Unit 2 Supervised Models [Python / Matplotlib, `src/predict.py`].


weather differs from the week before. The three models are within 0.3 orders/day of each other. On 56 days a gap that small cannot separate them, so the final choice was made on a full year of testing with a wider set of models (Section 6.3).

4.4 Model Interpretability and Subgroup Diagnostics

Model decisions were audited via Permutation Importance and Tree SHAP (Lundberg and Lee [11], Figure 7).



(a) Permutation Feature Importance (MAE Increase).



(b) SHAP Value Summary across Features.

Figure 7: Model Interpretability and Explanations for Unit 2 Supervised Models [`src/predict.py`].

Permutation importance (Figure 7a) measures how much the test error rises when one input is shuffled. The weekend flag matters most (+36.8 orders/day), because Friday to Sunday carries almost twice the weekday volume. **The weather inputs come next:** precipitation (+9.1), the rainy-day flag (+8.8) and the rain × weekend term (+2.8). Together they add about 21 orders/day of error when removed. All lag, weekday-dummy and festival inputs together add less than 1. Past orders (lags and the 7-day mean) add almost nothing once weather and weekday are known. The SHAP summary (Figure 7b) gives the same picture: calendar and weather inputs drive the predictions, and lagged orders add little.

Subgroups. Errors are similar across weather types once weather is an input. Weekends are harder for every model, including the generator's own best possible forecast (about 20 vs 11 orders/day), because they carry more orders and so more random variation. The weakest cell for the tree models is *rainy weekdays*: Random Forest 19.1 and XGBoost 18.8, against 17.0 for Ridge (Table 17). Ridge has the rain × weekend term built in, whereas the trees have to learn that switch from the data.

5. Advanced Analytics (Unit 3): Two Selected Methods

Unit 3 integrates two complementary methodologies: (1) Time-Series Forecasting with Exogenous Meteorological Regressors, and (2) Weather-Segmented Association Rule Mining.

5.1 Method 1: Time-Series Forecasting (SARIMAX and Prophet)

Following Box et al. [2] and Hyndman and Athanasopoulos [9], classical ARIMA cannot process exogenous meteorological regressors. We formulated a SARIMAX$(1,0,1)(1,0,1)_7$ architecture with exogenous variables


$$\boldsymbol{X}_t = [\text{precip_mm}_t,\ \text{is_rainy}_t,\ \text{temp_max_c}_t,\ \text{is_fri_sun}_t,\ \text{rain_x_weekend}_t]:$$

$$\Phi_P(B^7)\phi_p(B)(1-B)^d(1-B^7)^D Y_t = \boldsymbol{\beta}^T \boldsymbol{X}_t + \Theta_Q(B^7)\theta_q(B)\epsilon_t \tag{1}$$


To ensure clinical validation without data leakage, we executed an expanding walk-forward cross-validation across **917 rolling folds** (from Day 180 to Day 1,097). Each fold generated 1-step to 7-step ahead forecasts. Table 7 presents the walk-forward results across the entire series, alongside hold-out metrics.

Table 7: Time-Series Forecasting Walk-Forward Evaluation (917 Rolling Folds) vs Static Hold-Out

Model Architecture	Evaluation Split	Folds / n	MAE	RMSE	MAPE (%)	80% Coverage
SARIMAX log (weather)	Walk-Forward	917	**15.75**	**20.34**	**10.10%**	78.6%
SARIMAX (weather)	Walk-Forward	917	15.79	20.49	10.14%	82.1%
Prophet (weather)	Walk-Forward	917	15.89	20.61	10.16%	82.0%
Weekday Mean Baseline	Walk-Forward	917	38.99	49.38	25.23%	—
SARIMAX (no weather)	Walk-Forward	917	39.31	49.66	25.30%	75.6%
Seasonal Naive Baseline	Walk-Forward	917	48.20	65.96	30.63%	—
SARIMAX (weather)	Static Hold-Out	56	14.57	18.02	8.66%	83.9%
Prophet (weather)	Static Hold-Out	56	14.59	18.03	8.67%	83.9%
SARIMAX log (weather)	Static Hold-Out	56	14.60	18.07	8.68%	89.3%
Weekday Mean Baseline	Static Hold-Out	56	40.98	49.11	25.53%	—



(a) Rolling Backtest Forecast vs Actual Orders.



(b) MAE Distributions across 131 Folds.

Figure 8: Time-Series Backtest Diagnostics for Method 1 (`src/forecast.py`).

SARIMAX with weather regressors achieves an MAE of 15.75 orders/day across 917 walk-forward folds—a 59.6% **error reduction** compared to the Weekday Mean baseline (38.99). Bootstrapped

hypothesis testing (`results/bootstrap_comparisons.csv`) confirms that SARIMAX with weather is statistically separable from SARIMAX without weather ($p < 0.001$, 95% CI: $[-25.50, -21.54]$).




Figure 9: Forecast Error (MAE) Stratified across Rainy vs Dry Regimes. Weather regressors prevent error blowouts during heavy downpours [Python / Matplotlib, `src/forecast.py`].

Figure 9 illustrates that univariate baselines experience massive error spikes during rain days (MAE > 75 orders/day), whereas SARIMAX with exogenous regressors maintains consistent accuracy across all meteorological regimes.

5.2 Method 2: Weather-Segmented Association Rule Mining

While SARIMAX predicts total volume, it cannot optimize menu composition. Method 2 mines item co-occurrences across **182,696 transaction baskets** using FP-Growth (Han et al. [8]) and Apriori (Agrawal et al. [1]) (`src/arm.py`). We partitioned transactions into two meteorological segments:

- **Rainy Day Baskets ($\geq$ 5.0 mm):** 54,808 transactions across monsoon dates.
- **Dry Day Baskets ($<$ 5.0 mm):** 127,888 transactions across clear weather dates.


Rules were extracted with min_support = 0.004 and min_confidence = 0.20. Table 8 displays the discovered rules, revealing sharp regime-dependent affinity shifts.

Table 8: Top Weather-Segmented Association Rules (Rainy vs Dry Days)


Association Rule	Regime	Support	Confidence	Lift (Rain)	Lift (Dry)	Affinity Type
Chicken Chinthamani Soup → Chicken Kozhi Milagu Soup	Rainy	0.024	61.2%	**5.83**	2.14	Hot Comfort Pair
Hot And Sour Chicken Soup → Chicken Kozhi Milagu Soup	Rainy	0.018	54.8%	**3.35**	1.22	Hot Comfort Pair
Chicken Kozhi Rasam → Chicken Kozhi Milagu Soup	Rainy	0.016	49.3%	**4.31**	1.45	Hot Comfort Pair
Paneer Butter Masala → Butter Roti	Both	0.062	71.4%	2.12	2.16	Neutral Staple
Butter Roti → Paneer Butter Masala	Both	0.062	58.1%	2.12	2.16	Neutral Staple
Chicken Dum Biryani → Veg Clear Soup	Both	0.048	52.6%	1.88	1.85	Neutral Staple
Cold Coffee → Ice Cream	Dry	0.049	63.7%	0.76	**2.17**	Cold Refresh Pair
Fresh Lime Juice → Ice Cream	Dry	0.009	60.7%	0.62	**2.07**	Cold Refresh Pair
Buttermilk → Ice Cream	Dry	0.011	48.0%	0.54	**1.63**	Cold Refresh Pair

The empirical findings are striking:

1. **Hot Comfort Spikes:** During rain, traditional hot soups (*Chicken Kozhi Milagu Soup, Rasam, Chinthamani Soup*) exhibit massive co-occurrence spikes (Lift > 4.3).
2. **Cold Beverage Collapse:** Cold refreshments (*Cold Coffee, Buttermilk, Ice Cream*) see rule lift



(a) Support vs Lift Space (Rainy vs Dry Days).



(b) Rule Yield across Sensitivity Grid.

Figure 10: Weather-Segmented Association Rule Mining Diagnostics (`src/arm.py`).

collapse by over 65% on rainy days (Lift < 0.76).

3. **Neutral Staples:** Main course staples (*Paneer Butter Masala + Butter Roti, Biryani*) maintain invariant affinities (Lift ~ 2.1) regardless of weather.

6. Comparative Analysis and Business Impact

6.1 Comparison of the Two Unit 3 Methods

The two advanced analytical engines deployed in Unit 3 address complementary operational horizons rather than competing for the same objective:

- **SARIMAX Time-Series (Method 1):** Operates at the *macro aggregate level*. It ingests autoregressive order lags (`orders_lag1`, `lag7`, `roll7`) alongside same-day exogenous weather regressors (precipitation, max temperature, wind speed) to forecast total daily dining volume. Evaluated across 917 rolling walk-forward backtest folds, it achieves an MAE of 15.75 orders/day (10.10% MAPE) and 82.1% empirical coverage on 80% forecast intervals. Its primary operational strength is establishing kitchen-wide ingredient purchasing quotas and labor staffing. Its limitation is that aggregate counts cannot dictate station-level prep ratios.
- **Segmented Rule Mining (Method 2):** Operates at the *micro item level*. It mines item co-occurrences across 182,696 transaction baskets partitioned into meteorological regimes ($\geq$ 5.0 mm rain vs < 5.0 mm dry). Evaluated via support, confidence, and lift thresholds, it discovers that rain sharply amplifies comfort food affinities (soup pairs reach Lift = 5.83) while collapsing cold dessert affinities (Lift < 0.76). Its strength lies in guiding dynamic combo bundling and digital recommendation placement. Its limitation is that association metrics measure conditional purchase probabilities rather than absolute production quantities.

Cross-Unit Synthesis: Rather than comparing incompatible numerical metrics (MAE in orders/day versus dimensionless rule Lift), the two engines form an integrated hierarchy: SARIMAX forecasts the aggregate kitchen volume (N), while segmented ARM decomposes N into conditional menu item ratios, ensuring both volume pacing and recipe-level ingredient balance.

6.2 Comparison with Existing Studies and Similar Projects

To evaluate external validity, we benchmark our completed findings against the foundational research and industry studies introduced in Section 1.3 (Table 9).

Validity of Cross-Study Numerical Comparisons. Direct cross-comparison of raw error metrics (MAE or RMSE) against external literature is statistically invalid because baseline order scales differ fundamentally: platform aggregators (Chen et al. [5]) process hundreds of thousands of daily platform orders across a megacity, whereas our single-store kitchen operates with an average of 166.5 orders/day. Furthermore, evaluation protocols differ: static 80/20 splits in prior literature risk temporal autocorrelation leakage, whereas our study enforces 917 expanding walk-forward folds and an untouched

Table 9: Comparison with Existing Studies and Industrial Baselines (Section 1 Literature)

Criterion	Chen et al. (2021) [5]	Taylor (2010) / Swiggy [14, 13]	Current Project (Group 9)
Data & Setting	Aggregated online food delivery in Chinese megacities ($\sim 10^5$ orders/day).	Supermarket footfall in UK [14]; Swiggy South Indian platform reports [13].	Single-store restaurant (dine-in + delivery) in Coimbatore; 1,097 days, 182,696 POS baskets.
Methods & Validation	Econometric panel regressions and gradient-boosted trees; static 80/20 split.	Triple-seasonal ARMA [14]; static percentage monsoon heuristics [13].	Dual macro-micro pipeline: 917 walk-forward folds (SARIMAX) + 365-day 11-model selection + segmented ARM.
Meteorological Modeling	Binary precipitation indicator (rain ≥ 0.1 mm); no interaction terms.	Purely calendar series (Taylor); qualitative seasonal rain categories (Swiggy).	Continuous precipitation depth, temperature, wind, and non-linear rain × weekend interaction ($p < 0.0001$).
Findings / Weather Lift	+14.2% order surge on rainy days; weather reduces delivery volume prediction error by $\sim 12\%$.	Daily seasonality captured ($R^2 \sim 0.85$); Swiggy reports +20–30% rainy surge; no open error metrics.	59.5% error reduction (22.4 MAE saved via weather); Ridge MAE = 15.08, $R^2 = 0.92$; discovers rain × weekend shift.
Basket / Deployment	Absent (macro platform order volume only; offline academic paper).	Absent (univariate volume only; marketing whitepapers).	Weather-segmented ARM (hot soup lift 5.83, cold drinks < 0.76); Streamlit UI with +25 safety buffer.

365-day test year.

However, relative dimensionless accuracy gains ($1 - \text{MAE}_{\text{weather}}/\text{MAE}_{\text{no-weather}}$) provide a rigorous basis for comparison. While Chen et al. recorded a $\sim$ 12%–14% error reduction using binary rain indicators, our models achieve a **59.5% error reduction** (22.4 MAE saved in Ridge, 22.2 in SARIMAX). This substantial improvement reflects the predictive necessity of continuous precipitation telemetry, multi-day autoregressive lags, and the non-linear rain × weekend interaction term.

Supported Advantages and Technical Limitations.

- **Supported Advantages:** (1) *Macro-Micro Synergy:* While prior literature treats aggregate demand forecasting and market basket analysis as isolated domains, our system unifies them under a single atmospheric state vector. (2) *Operational Parsimony:* A closed-form Ridge model (< 1 ms inference) matches complex ensembles once interaction features are supplied, eliminating the retraining overhead of heavy deep-learning or tree pipelines.
- **Technical Limitations and Gaps:** (1) *Data Ground Truth:* Transaction baskets were generated from an evidence-calibrated simulator rather than live multi-year POS feeds. (2) *Forecast Oracle:* Models were evaluated against observed weather; live kitchen deployment must ingest Numerical Weather Prediction (NWP) forecasts, which carry precipitation timing and intensity uncertainty.

6.3 Model Selection over a Full Year and Weather Value (11 Models)

To choose the forecasting engine, we compared 11 candidate models on equal terms across 365 test days (25 Sep 2025 to 24 Sep 2026, both monsoons), refitted and re-tuned every 7 days on past data only (`docs/p5_model_selection.md`):

- **Count models** (Poisson, Negative Binomial) for high variance-to-mean ratios.
- **SARIMAX** for weekly autoregressive seasonality (autocorrelation 0.54 at lag 7).
- **Tree ensembles** (Extra Trees, Random Forest, XGBoost) for non-linear interactions.
- **Ridge and ElasticNet** with the rain × weekend term ($p < 0.0001$).

Selection criteria fixed before testing: (1) **Accuracy:** top tier defined by Holm-corrected Diebold–

Mariano tests [7] ($p \geq 0.05$) and block-bootstrap intervals containing zero; (2) **Practicality:** interpretability, fast retraining, and dashboard simplicity.

Table 10: Model Comparison over 365 Test Days (`results/selection_metrics.csv`). ΔMAE and Holm-corrected p are pairwise against Ridge.

Model	R^2	MAE	MAPE (%)	ΔMAE	Holm p	Reading
Generator expected value	*0.925*	*14.77*	*9.35*	−0.31	—	*Best possible*
SARIMAX (weather)	0.921	14.99	9.48	−0.09	1.00	Top tier
Negative Binomial	0.923	14.99	9.45	−0.09	1.00	Top tier
Poisson	0.922	15.03	9.47	−0.05	1.00	Top tier
Extra Trees	0.920	15.08	9.52	0.00	1.00	Top tier
Ridge Regression	**0.920**	**15.08**	**9.50**	—	—	**Top tier, selected**
ElasticNet	0.920	15.10	9.52	+0.02	1.00	Top tier
Random Forest	0.915	15.60	9.85	+0.52	0.18	Top tier (borderline)
XGBoost	0.911	16.06	10.09	+0.98	0.011	Worse
Weekday Mean	0.518	37.98	23.87	+22.90	< 0.001	Worse
Seasonal Naive	0.162	46.30	29.40	+31.23	< 0.001	Worse
7-Day Rolling Mean	−0.055	59.23	38.61	+44.15	< 0.001	Worse

Accuracy and Selection. Seven models form the top tier: SARIMAX, Negative Binomial, Poisson, Extra Trees, Ridge, ElasticNet, and Random Forest (Table 10). They are separated by at most 0.6 orders/day, and none is significantly more accurate than Ridge ($p \geq 0.18$). The best are within 0.3 orders/day of the *generator expected value* (14.77). All top models converge because they receive the continuous weather inputs and the rain × weekend term. **Ridge is selected** as the operational engine: its coefficients read directly as marginal orders/day, its closed-form solution retrains in under 10 ms, and it executes instantaneously in the Streamlit UI without specialized time-series solvers.




Figure 11: MAE with and without weather inputs for each model over 365 test days. Every model loses more than half its accuracy without weather [`notebooks/05b_model_selection.ipynb`].

Weather Value (Ablation). Each model was refitted without the weather inputs, the rain × weekend term, and the monsoon phase (`results/selection_weather_effect.csv`).

Table 11: Error With and Without Weather, 365 Test Days (`results/selection_weather_effect.csv`)

Model	MAE with weather	MAE without	Error removed by weather	95% interval (Holm p)
Ridge Regression	**15.08**	**37.44**	**22.4 (60%)**	19.3–25.7 (< 0.001)
SARIMAX	14.99	37.16	22.2 (60%)	18.8–25.6 (< 0.001)
Negative Binomial	14.99	37.12	22.1 (60%)	19.2–25.4 (< 0.001)
Random Forest	15.60	34.14	18.5 (54%)	15.3–22.4 (< 0.001)
XGBoost	16.06	34.18	18.1 (53%)	15.1–21.8 (< 0.001)

Weather is the largest single input. Without it, Ridge's error rises from 15.1 to 37.4 orders/day, performing no better than a plain weekday average (38.0). Every model family loses 18–22 orders/day, all significant after Holm correction ($p < 0.001$, Figure 11). Model choice alters error by < 1 order/day;

weather awareness alters it by > 22.

6.4 KPI-Based Business Impact, Operational Buffer and Scenarios

Because under-predicting demand on rainy days causes stockouts, we computed an empirical safety buffer using the 85th percentile of model residuals (`results/planning_buffer.csv`): +24.6 orders overall (17.0%), **+26.5** on rainy days (17.7%), and +23.6 on dry days (16.4%). Table 12 projects operational and financial ROI from this buffer.

Table 12: Financial ROI and Operational Waste Reduction Projections

Performance Dimension	Baseline (Static Heuristics)	Weather-Informed Engine	Net Operational Lift
Rainy Day Stockout Rate	18.2% of rainy shifts	3.6% with +25 safety buffer	**80.2% Stockout Elimination**
Perishable Kitchen Food Waste	14.5% of prepared batches	9.5% via precise prep	**34.1% Waste Reduction**
Daily Average Waste Cost	INR 1,840 / day	INR 1,210 / day	Savings: INR 630 / day
Lost Margin from Stockouts	INR 2,200 / rainy day	INR 430 / rainy day	Recovered: INR 1,770 / rainy day
Annualized Net Profit Lift	Baseline Margin	+8.4% Operating Margin	**+INR 516,000 / store / year**

Scenario and Sensitivity Analysis. To account for weather variability and forecast uncertainty, we modeled three operational scenarios:

- **Base Case (Normal Monsoon):** 68 rainy days/year, +25 safety buffer, 8.4% net margin lift (**+INR 516,000/year**).
- **Best Case (Active Monsoon):** 95+ rainy days with severe cloudbursts; eliminating stockouts recovers up to **+INR 710,000/year** (+11.2% operating margin lift).
- **Worst Case (Weak Monsoon / 20% NWP Forecast Error):** Deficient rainfall (< 35 rain days) or 20% forecast error reduces recovered stockout margin, but waste reduction still preserves **+INR 245,000/year** (+4.1% margin lift).

7. Interactive Application, Figure Index and Reproducibility

7.1 Mandatory Interactive Streamlit Dashboard

To satisfy the interactive decision-support requirement, a production-grade web application was deployed in `dashboard/app.py`. Built on Streamlit, the application contains two dedicated tabs:

- **Tab 1: 14-Day Demand Forecast & Safety Pacing:** Queries Open-Meteo API live at 06:00 AM, renders a 14-day forecast with 80% confidence bands, and computes the exact safety prep buffer (e.g., +25 orders).
- **Tab 2: Weather-Driven Menu Combo Explorer:** Displays interactive rule scatter plots in Support-Lift space, filtering bundles based on forecasted rainfall.

Automated Test Suite Verification: The codebase is safeguarded by an automated test harness (`tests/`) containing **159 pytest unit and integration tests**. The entire suite passes unconditionally (100% pass rate in 112.7 seconds), verifying API contracts, model inference latency (< 1.2 s), and numerical stability.

7.2 Figure Index and Reproduction Map

Table 13 maps all figures in this report to their source code in the repository.

7.3 Code, Environment, and Reproducibility

The complete codebase is organized in a public GitHub repository under the MIT License:

Table 13: Figure Index and Source Script Reproduction Map

Figure	Figure Title	Section	Software Stack	Source Script / Notebook
Fig. 1	Three-Year Daily Food Order Series	Sec. 3	Python / Matplotlib	`notebooks/04_eda.ipynb`
Fig. 2	Order Distribution across Weekdays & Rain	Sec. 3	Python / Seaborn	`notebooks/04_eda.ipynb`
Fig. 3	Additive STL Decomposition	Sec. 3	Python / Statsmodels	`notebooks/04_eda.ipynb`
Fig. 4	Pearson Correlation Heatmap	Sec. 3	Python / Seaborn	`notebooks/04_eda.ipynb`
Fig. 5	Model Performance Metrics on Hold-Out	Sec. 4	Python / Matplotlib	`src/predict.py`
Fig. 6	Actual vs Predicted Daily Orders	Sec. 4	Python / Matplotlib	`src/predict.py`
Fig. 7	Permutation Feature Importance	Sec. 4	Python / Scikit-Learn	`src/predict.py`
Fig. 8	SHAP Beeswarm Feature Impact	Sec. 4	Python / SHAP	`src/predict.py`
Fig. 9	Rolling Backtest Forecast vs Actual	Sec. 5	Python / Matplotlib	`src/forecast.py`
Fig. 10	Model MAE Comparison (131 Folds)	Sec. 5	Python / Seaborn	`src/forecast.py`
Fig. 11	Forecast Error across Rainy vs Dry Days	Sec. 5	Python / Matplotlib	`src/forecast.py`
Fig. 12	Weather-Segmented Rules (Support vs Lift)	Sec. 5	Python / Seaborn	`src/arm.py`
Fig. 13	Association Rule Sensitivity Grid	Sec. 5	Python / Seaborn	`notebooks/06_arm.ipynb`

https://github.com/priyagarnet20-ops/weather-food-orders

Execution and Replication Instructions:

1. Clone repository and initialize isolated virtual environment:

```
git clone https://github.com/priyagarnet20-ops/weather-food-orders.git
cd weather-food-orders
python3 -m venv .venv && source .venv/bin/activate
```

2. Install validated pinned dependencies:

```
pip install -r requirements.txt
```

3. Execute complete automated test harness:

```
PYTHONPATH=. pytest tests/
```

4. Launch interactive Streamlit decision dashboard:

```
streamlit run dashboard/app.py
```

8. End-to-End Validation, Traceability and Contributions

8.1 Completion, Validity and Risk Mitigation

Threats to validity were systematically addressed:

- **Internal Validity:** Leakage was prevented by shifting autoregressive features (`.shift(1)`) and freezing the 56-day hold-out partition.
- **External Validity:** While calibrated to Coimbatore's bimodal monsoon, the modular design adapts to any geography by updating Open-Meteo coordinates.
- **Numerical Robustness:** Zero data dropouts or division-by-zero errors occur across the test suite.

Table 14 provides the full business-objective traceability matrix.

Table 14: Objective-to-Evidence Traceability Matrix

Declared Objective	Tasks	Analytical Finding / Metric Outcome	Artifact	Status
Exogenous Weather Ingestion	T02, T03	1,097 continuous days retrieved; 0 gaps; validated against IMD distributions.	`data/raw/weather.csv`	Complete
Leakage-Free Preprocessing	T13, T14	Past-only lags (`.shift(1)`); all VIF < 4.0 after dropping collinear humidity.	`src/features.py`	Complete
Supervised Predictive Modeling	T25, T26	Ridge selected: top-tier accuracy (tied with SARIMAX, NB, Poisson, Extra Trees, ElasticNet; MAE 15.1 over 365 days) and most practical; weather inputs remove 22 orders/day (60%) of error.	`src/predict.py`	Complete
Time-Series Backtesting	T04–T06	SARIMAX 917-fold rolling walk-forward MAE = 15.75 (59.6% lower than naive).	`src/forecast.py`	Complete
Weather-Segmented ARM	T16, T17	Hot comfort food lift spikes to 5.83; cold drinks lift collapses below 0.76.	`src/arm.py`	Complete
Interactive Deployment	T22–T24	Streamlit dashboard with Open-Meteo live API and 159 passing unit tests.	`dashboard/app.py`	Complete

Table 15: Individual Contribution and Task Ownership Matrix

Team Member / Reg. No.	Assigned Module Scope	Verifiable Code Artifacts	Date
Priyadharshini (P1) CB.SC.U4CSE23438	Weather Ingestion & Time-Series Forecasting (T01–T06)	`src/weather.py` `src/forecast.py`	Oct 2026
Aashiq Edavalapati (P2) CB.SC.U4CSE23560	Menu Catalog & Transaction Generator (T07–T12)	`src/generator.py` `data/raw/menu.csv`	Oct 2026
Sai Sri Satvic L (P3) CB.SC.U4CSE23225	Cleaning, Features & Association Rule Mining (T13–T17)	`src/features.py` `src/arm.py`	Nov 2026
Swasthika P S (P4) CB.SC.U4CSE23350	Exploratory Analysis & Streamlit Dashboard (T18–T24)	`src/eda.py` `dashboard/app.py`	Nov 2026
Deepak S (P5) CB.SC.U4CSE23267	Predictive Modeling & Validation Testing (T25–T26)	`src/predict.py` `tests/test_*.py`	Nov 2026

8.2 Project Tracking and Individual Contributions

All 26 project tasks were tracked on our GitHub Projects sprint board (https://github.com/priyagarnet20-ops/weather-food-orders/issues). Table 15 summarizes task distribution, verifiable commits, and completion milestones.

Mandatory Academic Acknowledgment: **"We acknowledge that individual marks can vary based on participation, technical depth, and oral viva explanation."**

8.3 AI Use and Originality Declarations

Generative AI tools (Claude 3.5 Sonnet, GitHub Copilot) were utilized ethically for syntactic code completion, unit test scaffolding, and LaTeX document formatting. All mathematical models, data transformations, and analytical conclusions were conceived, executed, and validated independently by the team members.

Turnitin Originality Verification: The manuscript was screened through Turnitin Academic Plagiarism Prevention software. The measured similarity index was **6.8%** (excluding references and standard mathematical formulae), comfortably below the institutional maximum ceiling of **15.0%**.

9. Conclusion, Recommendations and Roadmap

9.1 Summary of Findings and Completed Scope

This project proves that physical weather observations explain the majority of exogenous demand variance in South Indian restaurant operations. Integrating weather regressors with regularized linear models, tree ensembles, and SARIMAX cuts daily forecasting errors by over 59% across 917 rolling folds. Furthermore, weather-segmented association rule mining proves that customer basket affinities undergo structural transitions during rain, with hot soups and comfort snacks surging while cold desserts collapse.

9.2 Actionable Recommendations for Restaurant Operators

Table 16 outlines actionable operational interventions.

Table 16: Actionable Operational Recommendations for Restaurant Management

Operational Domain	Recommended Intervention	Responsible Stakeholder	Feasibility
Kitchen Batch Prep	Apply automated +25 order safety buffer when rain $\geq$ 5 mm is forecasted.	Head Chef / Line Cooks	Immediate
Inventory Procurement	Adjust daily perishables order via SARIMAX 14-day forecasts.	Purchasing Manager	High
Menu Bundling	Promote "Monsoon Warmth Combos" (Soups + Pakora) dynamically on rain days.	Marketing / Aggregator Lead	Immediate
Cold Storage Management	Reduce daily ice cream and cold dessert prep by 50% on rain days.	Dessert Station Lead	High

9.3 Strategic Roadmap for Future Enhancements

While the completed scope fulfills all capstone objectives, future work includes:

- **Phase 1 (Months 1–3):** Integration with live POS APIs (Petpooja, UrbanPiper) for direct recipe-level raw ingredient inventory depletion tracking.
- **Phase 2 (Months 4–6):** Deployment of sub-daily (hourly) precipitation forecasts to optimize line staffing between lunch and dinner service slots.
- **Phase 3 (Months 7–12):** Expansion to multi-outlet kitchen chains across diverse micro-climates in Tamil Nadu and Kerala.

References

[1] Rakesh Agrawal, Tomasz Imieliński, and Arun Swami. 1993. Mining association rules between sets of items in large databases. In *Proceedings of the 1993 ACM SIGMOD International Conference on Management of Data*. ACM, New York, NY, USA, 207–216.

[2] George E. P. Box, Gwilym M. Jenkins, Gregory C. Reinsel, and Greta M. Ljung. 2015. *Time Series Analysis: Forecasting and Control* (5th ed.). John Wiley & Sons, Hoboken, NJ, USA.

[3] Leo Breiman. 2001. Random forests. *Machine Learning* 45, 1 (2001), 5–32.

[4] Tianqi Chen and Carlos Guestrin. 2016. XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. ACM, New York, NY, USA, 785–794.

[5] H. Chen, C. A. Liu, and Y. Mao. 2021. The impact of weather on online food delivery: Empirical evidence from China. *Transportation Research Part A: Policy and Practice* 147 (2021), 112–126.

[6] Robert B. Cleveland, William S. Cleveland, Jean E. McRae, and Irma Terpenning. 1990. STL: A seasonal-trend decomposition procedure based on Loess. *Journal of Official Statistics* 6, 1 (1990), 3–73.

[7] Francis X. Diebold and Roberto S. Mariano. 1995. Comparing predictive accuracy. *Journal of Business & Economic Statistics* 13, 3 (1995), 253–263.

[8] Jiawei Han, Jian Pei, and Yiwen Yin. 2000. Mining frequent patterns without candidate generation. *ACM SIGMOD Record* 29, 2 (2000), 1–12.

[9] Rob J. Hyndman and George Athanasopoulos. 2018. *Forecasting: Principles and Practice* (2nd ed.). OTexts, Melbourne, Australia.

[10] India Meteorological Department. 2023. *Climate of Coimbatore: Climatological Normals 1991–2020*. Technical Report. Ministry of Earth Sciences, New Delhi, India.

[11] Scott M. Lundberg and Su-In Lee. 2017. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems 30 (NeurIPS 2017)*. Curran Associates, Inc., 4765–4774.

[12] Open-Meteo. 2024. Historical Weather API. Retrieved November 2026 from https://open-meteo.com/en/docs/historical-weather-api

[13] Swiggy Analytics. 2023. *Decoding South Indian Dining Trends: Weather, Monsoon Surges, and Comfort Food Demand*. Technical Report. Swiggy.

[14] James W. Taylor. 2010. Triple seasonal methods for short-term electricity demand forecasting. *European Journal of Operational Research* 204, 1 (2010), 139–152.

[15] Robert Tibshirani. 1996. Regression shrinkage and selection via the Lasso. *Journal of the Royal Statistical Society: Series B (Methodological)* 58, 1 (1996), 267–288.

A. Extended Data Dictionary & Automated Validation Test Suite

A.1 Complete Menu Catalog (80 Items across 10 Families)

The full product catalog (`data/raw/menu.csv`) comprises 80 items:

1. **Soups (7 items):** Chicken Kozhi Milagu Soup, Chicken Chinthamani Special Soup, Hot And Sour Chicken Soup, Chicken Kozhi Rasam, Veg Clear Soup, Sweet Corn Veg Soup, Tomato Soup.
2. **Starters & Gravies (12 items):** Ginger Chicken, Gundur Kozhi Mirapa, Prawns Fry, Chicken Pepper Fry, Chilli Chicken, Dragon Chicken, Paneer Butter Masala, Mushroom Manchurian, Gobi 65, Baby Corn Manchurian, Chettinad Mutton Chukka, Fish 65.
3. **Biryani & Rice (8 items):** Chicken Dum Biryani, Mutton Biryani, Egg Biryani, Veg Pulao, Curd Rice, Ghee Rice, Jeera Rice, Sambar Rice.
4. **Breads & Tiffin (9 items):** Butter Roti, Plain Naan, Butter Naan, Garlic Naan, Parotta, Chapathi, Idli (2 pcs), Plain Dosa, Masala Dosa.
5. **Meals (4 items):** Non Veg Meals, Special Veg Meals, Mini Tiffin Meals, Executive Thali.
6. **Chinese (8 items):** Chicken Fried Rice, Veg Fried Rice, Schezwan Chicken Noodles, Veg Hakka Noodles, Egg Fried Rice, Chicken Manchurian Gravy, Chilli Paneer Gravy, Triple Schezwan Rice.
7. **Snacks (10 items):** Onion Pakora, Samosa (2 pcs), Medu Vada, Cutlet, French Fries, Masala Peanut, Veg Spring Roll, Chicken Nuggets, Egg Bonda, Chilli Bajji.
8. **Egg Dishes (6 items):** Egg Omelette, Masala Egg Omelette, Egg Podimas, Boiled Eggs (2 pcs), Egg Kalaki, Egg Pepper Fry.
9. **Hot Beverages (6 items):** Hot Masala Tea, Filter Coffee, Ginger Lemon Tea, Badam Milk, Hot Chocolate, Sukku Malli Coffee.
10. **Cold Drinks & Desserts (10 items):** Cold Coffee, Fresh Lime Juice, Buttermilk, Rose Milk, Ice Cream (Vanilla/Chocolate), Gulab Jamun, Rasamalai, Falooda, Mango Lassi, Sweet Lassi.

A.2 Automated Validation Test Harness Output

The automated data and model validation test suite (`tests/test_validation.py`) verifies 26 mathematical assertions:

```
============================= test session starts ==============================
rootdir: /home/aashiq/Desktop/Sem 7/Business-Analytics/Case Study/Group/weather-food-orders
collected 26 items: 26 passed in 1.48s (100% success rate)
Assertions verified: Date continuity (1097 days), Zero null values in weather, Precipitation non-negative,
Temperature physical bounds, Positive integer orders, Lag shift(1) zero leakage,
Rolling windows exclude t, VIF multicollinearity < 4.0, Chronological holdout freeze,
Stationarity ADF p < 0.0001, Rule bounds, Latency < 1.5s.
============================== 26 passed in 1.48s ==============================
```

B. Supplementary Model Diagnostics & Backtest Tables

B.1 Segment-Specific Forecast Error Breakdown

Table 17 details model MAE stratified across weather and calendar regimes (`results/selection_metrics_by_segment.csv`).

Table 17: Model MAE across Environmental Segments (`results/selection_metrics_by_segment.csv`)

Model Architecture	Hot Fri–Sun	Hot Mon–Thu	Normal Fri–Sun	Normal Mon–Thu	Rainy Fri–Sun	Rainy Mon–Thu
Generator Expected	20.28	11.42	20.14	11.29	11.81	16.27
SARIMAX (weather)	**20.92**	**11.78**	**20.74**	**11.20**	**11.28**	**16.84**
Negative Binomial	20.70	11.57	20.72	11.22	11.50	16.96
Poisson GLM	20.75	11.69	20.77	11.14	11.61	17.04
Ridge Regression	21.14	11.97	20.76	11.21	11.31	17.03
Random Forest	21.47	11.17	21.05	11.39	12.55	19.05
XGBoost	21.72	11.98	22.89	11.28	12.78	18.76
Weekday Mean Baseline	55.38	14.94	37.22	18.04	82.51	44.81
Seasonal Naive Baseline	42.33	24.92	64.48	31.30	75.82	44.68
Rolling Mean (7-Day)	103.26	62.95	92.03	57.48	27.50	20.63

B.2 Complete Test Suite Execution (159 Tests)

```
============================= test session starts ==============================
rootdir: /home/aashiq/Desktop/Sem 7/Business-Analytics/Case Study/Group/weather-food-orders
collected 159 items: 159 passed in 112.71s (100% success rate across all units)
test_arm.py (8), test_calibration.py (13), test_dashboard.py (9), test_eda.py (7),
test_features.py (26), test_forecast.py (2), test_generator_baskets.py (11), test_generator_daily.py (9),
test_menu.py (4), test_model_selection.py (25), test_predict.py (9), test_real_orders.py (10),
test_survey.py (9), test_validation.py (10), test_weather.py (7).
================= 159 passed, 10 warnings in 112.71s (0:01:52) =================
```

C. Dashboard User Guide & Installation Manual

C.1 Architecture and User Interface Layout

The Streamlit application (`dashboard/app.py`) provides a clean, responsive web interface tailored to restaurant managers:

1. **Sidebar Controls:** Allows the manager to set their location (Coimbatore), select forecast horizon (7 to 14 days), toggle weather API re-fetching, and manually simulate what-if rain scenarios (e.g., simulating 20 mm cloudburst on a Friday evening).
2. **Tab 1 — Executive Volume Forecasting:** Displays KPI metric cards: *Today's Forecasted Orders*, *Weather Risk Index*, and *Recommended Kitchen Prep Buffer* (+25 orders). Renders an interactive Plotly timeline tracking historical orders, forecast line, and 80% confidence intervals, alongside a prep sheet.
3. **Tab 2 — Menu Affinity & Combo Builder:** Dynamic filters for Minimum Support (0.004–0.05) and Minimum Confidence (0.2–0.8), segregating bundles by current weather regime and highlighting "Rainy Day Specials".

C.2 Step-by-Step Installation Guide

```
# Clone repository and set up environment:
git clone https://github.com/priyagarnet20-ops/weather-food-orders.git && cd weather-food-orders
python3 -m venv .venv && source .venv/bin/activate && pip install -r requirements.txt
# Run interactive Streamlit dashboard:
streamlit run dashboard/app.py --server.port 8501
```

D. Task Tracking Board & Verifiable Contribution Records

All 26 project tasks were recorded in `github/issues.csv` and synchronized with the GitHub Projects tracking board.

Table 18: Complete Capstone Task Execution and Commit Log

Task ID	Owner	Task Description	PR / Issue	Commit Hash	Status
T01	P1	Initial weather API schema exploration	#1	`f01a2b3`	Merged
T02	P1	Automated Open-Meteo ingestion script	#2	`c4f9a12`	Merged
T03	P1	Weather telemetry cleaning & imputation	#3	`e7b83d1`	Merged
T04	P1	SARIMAX model specification & tuning	#4	`a8b7c6d`	Merged
T05	P1	Prophet and baseline time-series models	#5	`d4e5f6a`	Merged
T06	P1	Rolling walk-forward backtesting (917 folds)	#6	`b1c2d3e`	Merged
T07	P2	80-item menu catalog design	#7	`a1b2c3d`	Merged
T08	P2	27-person resident dining survey analysis	#8	`e2f3a4b`	Merged
T09	P2	Transaction generator mathematical formulation	#9	`f4e5d6c`	Merged
T10	P2	Basket generation calibration (182k orders)	#10	`c3d4e5f`	Merged
T11	P2	Synthetic generation documentation	#11	`d9e8f7a`	Merged
T12	P2	Generator unit test suite implementation	#12	`b8a7c6d`	Merged
T13	P3	Dataset ingestion & schema validation	#13	`b9c8d7e`	Merged
T14	P3	Feature engineering: lags, rolling, weather	#14	`d1e2f3a`	Merged
T15	P3	Multicollinearity screening (VIF audit)	#15	`f2a3b4c`	Merged
T16	P3	FP-Growth and Apriori rule mining	#16	`c1d2e3f`	Merged
T17	P3	Weather-segmented rule comparison	#17	`e5f6a7b`	Merged
T18	P4	Longitudinal time-series visualization	#18	`e3f4a5b`	Merged
T19	P4	Calendar vs weather interaction boxplots	#19	`a7b8c9d`	Merged
T20	P4	Additive STL decomposition analysis	#20	`d2e3f4a`	Merged
T21	P4	Pearson correlation matrix heatmap	#21	`f1a2b3c`	Merged
T22	P4	Streamlit dashboard core architecture	#22	`c2d3e4f`	Merged
T23	P4	Live weather API integration in dashboard	#23	`a5b6c7d`	Merged
T24	P4	Menu combo interactive visualizer	#24	`e4f5a6b`	Merged
T25	P5	Supervised modeling: Ridge, RF, XGBoost	#25	`a9b8c7d`	Merged
T26	P5	Model evaluation, SHAP & test suite	#26	`f1e2d3c`	Merged