

## Assignment4: Ex10

### Creating Database:

```
MySQL 8.0 Command Line Client
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 22
Server version: 8.0.28-commercial MySQL Enterprise Server - Commercial

Copyright (c) 2000, 2022, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> CREATE DATABASE PRIYA_8020951;
Query OK, 1 row affected (0.08 sec)

mysql> SHOW DATABASES;
+-----+
| Database                |
+-----+
| djangodb                 |
| information_schema       |
| mysampled               |
| mysql                    |
| performance_schema       |
| priya_8020951            |
| sys                      |
+-----+
7 rows in set (0.07 sec)

mysql> USE PRIYA_8020951;
Database changed
```

### Creating tables:

```
MySQL 8.0 Command Line Client
-> id INT NOT NULL AUTO_INCREMENT,
-> origin VARCHAR(15) NOT NULL,
-> destination VARCHAR(15) NOT NULL,
-> duration INT NOT NULL,
-> PRIMARY KEY(id)
-> );
Query OK, 0 rows affected (1.42 sec)

mysql> CREATE TABLE flights_noIndex(
-> id INT NOT NULL,
-> origin TEXT NOT NULL,
-> destination TEXT NOT NULL,
-> duration INTEGER NOT NULL,
-> );
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ');' at line 5
mysql> CREATE TABLE flights_noIndex(
-> id INT NOT NULL,
-> origin TEXT NOT NULL,
-> destination TEXT NOT NULL,
-> duration INTEGER NOT NULL
-> );
Query OK, 0 rows affected (0.83 sec)

mysql> INSERT INTO FLIGHTS
-> (origin,destination,duration)
-> VALUES("New York","London", 415);
Query OK, 1 row affected (0.38 sec)

mysql> (origin,destination,duration)
```

Inserting values:

```
MySQL 8.0 Command Line Client
mysql> INSERT INTO FLIGHTS
      -> (origin,destination,duration)
      -> VALUES("New York","London",415);
Query OK, 1 row affected (0.10 sec)

mysql> INSERT INTO FLIGHTS
      -> (origin,destination,duration)
      -> VALUES("Shanghai","Paris",760);
Query OK, 1 row affected (0.13 sec)

mysql> INSERT INTO FLIGHTS
      -> (origin,destination,duration)
      -> VALUES("Istanbul","Tokyo",700);
Query OK, 1 row affected (0.11 sec)

mysql> INSERT INTO FLIGHTS
      -> (origin,destination,duration)
      -> VALUES("New York","Paris",435);
Query OK, 1 row affected (0.12 sec)

mysql> INSERT INTO FLIGHTS
      -> (origin,destination,duration)
      -> VALUES("Moscow","Paris",245);
Query OK, 1 row affected (0.11 sec)

mysql> INSERT INTO FLIGHTS
      -> (origin,destination,duration)
      -> VALUES("Lima","New York",455);
Query OK, 1 row affected (0.12 sec)
```

Select statements

# MySQL 8.0 Command Line Client

```
-> VALUES("Lima","New York",455);  
Query OK, 1 row affected (0.12 sec)
```

```
mysql> select * from flights WHERE id=3;
```

```
+-----+-----+  
| id | origin | destination | duration |  
+-----+-----+  
| 3 | Istanbul | Tokyo | 700 |  
+-----+-----+  
1 row in set (0.03 sec)
```

```
mysql> select * from flights WHERE origin="New York";
```

```
+-----+-----+  
| id | origin | destination | duration |  
+-----+-----+  
| 1 | New York | London | 415 |  
| 4 | New York | Paris | 435 |  
+-----+-----+  
2 rows in set (0.04 sec)
```

```
mysql> select * from flights WHERE duration>500;
```

```
+-----+-----+  
| id | origin | destination | duration |  
+-----+-----+  
| 2 | Shanghai | Paris | 760 |  
| 3 | Istanbul | Tokyo | 700 |  
+-----+-----+  
2 rows in set (0.00 sec)
```

```
mysql> select * from flights WHERE duration>500 AND destination = "Paris";
```

```
+-----+-----+  
| id | origin | destination | duration |  
+-----+-----+  
| 2 | Shanghai | Paris | 760 |  
+-----+-----+  
1 row in set (0.00 sec)
```

```
mysql> select * from flights WHERE duration>500 OR destination = "Paris";
```

```
+-----+-----+  
| id | origin | destination | duration |  
+-----+-----+  
| 2 | Shanghai | Paris | 760 |  
| 3 | Istanbul | Tokyo | 700 |  
| 4 | New York | Paris | 435 |  
| 5 | Moscow | Paris | 245 |  
+-----+-----+  
4 rows in set (0.00 sec)
```

```
mysql>
```

## MySQL 8.0 Command Line Client

```
mysql> select * from flights WHERE origin IN ("New York", "Lima");
```

id	origin	destination	duration
1	New York	London	415
4	New York	Paris	435
6	Lima	New York	455

```
3 rows in set (0.00 sec)
```

```
mysql> select * from flights WHERE origin LIKE "%a%";
```

id	origin	destination	duration
2	Shanghai	Paris	760
3	Istanbul	Tokyo	700
6	Lima	New York	455

```
3 rows in set (0.00 sec)
```

```
mysql> select DISTINCT origin, destination FROM flights WHERE origin IN("New York","Lima");
```

origin	destination
New York	London
New York	Paris
Lima	New York

```
3 rows in set (0.01 sec)
```

```
mysql> select DISTINCT origin FROM flights WHERE origin IN("New York","Lima");
```

origin
New York
Lima

```
2 rows in set (0.00 sec)
```

```
mysql> select * FROM flights LIMIT 5;
```

id	origin	destination	duration
1	New York	London	415
2	Shanghai	Paris	760
3	Istanbul	Tokyo	700
4	New York	Paris	435
5	Moscow	Paris	245

## MySQL 8.0 Command Line Client

```
mysql> select * from flights order by duration;
```

id	origin	destination	duration
5	Moscow	Paris	245
1	New York	London	415
4	New York	Paris	435
6	Lima	New York	455
3	Istanbul	Tokyo	700
2	Shanghai	Paris	760

6 rows in set (0.00 sec)

```
mysql> SELECT Origin, count(duration) from flights GROUP BY origin;
```

Origin	count(duration)
New York	2
Shanghai	1
Istanbul	1
Moscow	1
Lima	1

5 rows in set (0.06 sec)

```
mysql> SELECT Origin, count(duration) from flights GROUP BY origin having count(duration)>2;  
Empty set (0.03 sec)
```

```
mysql> SELECT Origin, count(duration) from flights GROUP BY origin having count(duration)=2;
```

Origin	count(duration)
New York	2

1 row in set (0.00 sec)

```
mysql> SELECT Origin, count(duration) from flights GROUP BY origin having count(duration)<2;
```

Origin	count(duration)
Shanghai	1
Istanbul	1
Moscow	1
Lima	1

4 rows in set (0.00 sec)

```
mysql>
```

Update and delete:

```

mysql> UPDATE flights
    -> SET duration = 430
    -> WHERE origin = "New York"
    -> AND destination = "London";
Query OK, 1 row affected (0.12 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> Select * from flights
    -> ;
+-----+-----+-----+
| id | origin | destination | duration |
+-----+-----+-----+
| 1 | New York | London | 430 |
| 2 | Shanghai | Paris | 760 |
| 3 | Istanbul | Tokyo | 700 |
| 4 | New York | Paris | 435 |
| 5 | Moscow | Paris | 245 |
| 6 | Lima | New York | 455 |
+-----+-----+-----+
6 rows in set (0.03 sec)

mysql> DELETE FROM flights WHERE destination = "Tokyo";
Query OK, 1 row affected (0.13 sec)

mysql> Select * from flights;
+-----+-----+-----+
| id | origin | destination | duration |
+-----+-----+-----+
| 1 | New York | London | 430 |
| 2 | Shanghai | Paris | 760 |
| 4 | New York | Paris | 435 |
| 5 | Moscow | Paris | 245 |
| 6 | Lima | New York | 455 |
+-----+-----+-----+
5 rows in set (0.00 sec)

mysql>

```

Aggregate functions:

```

MySQL 8.0 Command Line Client
mysql> select AVG(duration) from flights;
+-----+
| AVG(duration) |
+-----+
|          501.6667 |
+-----+
1 row in set (0.03 sec)

mysql> select COUNT(duration) from flights;
+-----+
| COUNT(duration) |
+-----+
|                6 |
+-----+
1 row in set (0.00 sec)

mysql> select COUNT(duration) from flights where origin="New York";
+-----+
| COUNT(duration) |
+-----+
|                2 |
+-----+
1 row in set (0.00 sec)

mysql> select SUM(duration) from flights;
+-----+
| SUM(duration) |
+-----+
|          3010 |
+-----+
1 row in set (0.00 sec)

mysql> select MIN(duration) from flights;
+-----+
| MIN(duration) |
+-----+
|          245 |
+-----+
1 row in set (0.06 sec)

mysql> select MAX(duration) from flights;
+-----+
| MAX(duration) |
+-----+
|          760 |
+-----+
1 row in set (0.00 sec)

mysql>

```

Commit & Rollback



# MySQL 8.0 Command Line Client

```
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> INSERT INTO flights
-> (origin,destination,duration)
-> VALUES("Chennai","Delhi",2);
Query OK, 1 row affected (0.04 sec)
```

```
mysql> COMMIT;
Query OK, 0 rows affected (0.07 sec)
```

```
mysql> SET AUTOCOMMIT=0;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> select * from flights;
+----+-----+-----+-----+
| id | origin | destination | duration |
+----+-----+-----+-----+
| 1 | New York | London | 430 |
| 2 | Shanghai | Paris | 760 |
| 4 | New York | Paris | 435 |
| 5 | Moscow | Paris | 245 |
| 6 | Lima | New York | 455 |
| 7 | Chennai | Mumbai | 2 |
| 8 | Mumbai | Chennai | 2 |
| 9 | Chennai | Delhi | 2 |
+----+-----+-----+-----+
8 rows in set (0.04 sec)
```

```
mysql> DELETE from flights WHERE destination="Delhi";
ERROR 1054 (42S22): Unknown column 'destination' in 'where clause'
mysql> DELETE from flights WHERE destination="Delhi";
Query OK, 1 row affected (0.05 sec)
```

```
mysql> Select * from flights;
+----+-----+-----+-----+
| id | origin | destination | duration |
+----+-----+-----+-----+
| 1 | New York | London | 430 |
| 2 | Shanghai | Paris | 760 |
| 4 | New York | Paris | 435 |
| 5 | Moscow | Paris | 245 |
| 6 | Lima | New York | 455 |
| 7 | Chennai | Mumbai | 2 |
| 8 | Mumbai | Chennai | 2 |
+----+-----+-----+-----+
7 rows in set (0.00 sec)
```

```
mysql>
```

## MySQL 8.0 Command Line Client

5	Moscow	Paris	245
6	Lima	New York	455
7	Chennai	Mumbai	2
8	Mumbai	Chennai	2
9	Chennai	Delhi	2

8 rows in set (0.04 sec)

```
mysql> DELETE from flights WHERE destination="Delhi";
ERROR 1054 (42S22): Unknown column 'destination' in 'where clause'
mysql> DELETE from flights WHERE destination="Delhi";
Query OK, 1 row affected (0.05 sec)
```

```
mysql> Select * from flights;
```

id	origin	destination	duration
1	New York	London	430
2	Shanghai	Paris	760
4	New York	Paris	435
5	Moscow	Paris	245
6	Lima	New York	455
7	Chennai	Mumbai	2
8	Mumbai	Chennai	2

7 rows in set (0.00 sec)

```
mysql> Rollback;
Query OK, 0 rows affected (0.05 sec)
```

```
mysql> Select * from flights;
```

id	origin	destination	duration
1	New York	London	430
2	Shanghai	Paris	760
4	New York	Paris	435
5	Moscow	Paris	245
6	Lima	New York	455
7	Chennai	Mumbai	2
8	Mumbai	Chennai	2
9	Chennai	Delhi	2

8 rows in set (0.00 sec)

```
mysql>
```

## Joins

(Full outer join is not supporting on SQL, used Union instead)

```
MySQL 8.0 Command Line Client
mysql> Select * from PASSANGER
-> ;
+-----+-----+-----+-----+
| id | Fname | lname | flight_id |
+-----+-----+-----+-----+
| 1 | Harry | Potter | 1 |
| 2 | ROn | Weasley | 1 |
| 3 | Hermione | Granger | 2 |
| 4 | Draco | Malfoy | 4 |
| 5 | Luna | Lovegood | 6 |
| 6 | Ginny | Weasley | 6 |
+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql> SELECT flight_id,fname,lname,origin,destination
-> FROM flights JOIN PASSANGER
-> ON PASSANGER.flight_id = flights.id;
+-----+-----+-----+-----+-----+
| flight_id | fname | lname | origin | destination |
+-----+-----+-----+-----+-----+
| 1 | Harry | Potter | New York | London |
| 1 | ROn | Weasley | New York | London |
| 2 | Hermione | Granger | Shanghai | Paris |
| 4 | Draco | Malfoy | New York | Paris |
| 6 | Luna | Lovegood | Lima | New York |
| 6 | Ginny | Weasley | Lima | New York |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql> SELECT flight_id,fname,lname,origin,destination
-> FROM flights RIGHT OUTER JOIN PASSANGER
-> ON PASSANGER.flight_id = flights.id;
+-----+-----+-----+-----+-----+
| flight_id | fname | lname | origin | destination |
+-----+-----+-----+-----+-----+
| 1 | Harry | Potter | New York | London |
| 1 | ROn | Weasley | New York | London |
| 2 | Hermione | Granger | Shanghai | Paris |
| 4 | Draco | Malfoy | New York | Paris |
| 6 | Luna | Lovegood | Lima | New York |
| 6 | Ginny | Weasley | Lima | New York |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql>
```

# MySQL 8.0 Command Line Client

```
mysql> SELECT flight_id,fname,lname,origin,destination
-> FROM flights RIGHT OUTER JOIN PASSANGER
-> ON PASSANGER.flight_id = flights.id
-> UNION
-> SELECT flight_id,fname,lname,origin,destination
-> FROM flights LEFT OUTER JOIN PASSANGER
-> ON PASSANGER.flight_id = flights.id;
```

flight_id	fname	lname	origin	destination
1	Harry	Potter	New York	London
1	RON	Weasley	New York	London
2	Hermione	Granger	Shanghai	Paris
4	Draco	Malfoy	New York	Paris
6	Luna	Lovegood	Lima	New York
6	Ginny	Weasley	Lima	New York
NULL	NULL	NULL	Moscow	Paris
NULL	NULL	NULL	Chennai	Mumbai
NULL	NULL	NULL	Mumbai	Chennai
NULL	NULL	NULL	Chennai	Delhi

10 rows in set (0.20 sec)

```
mysql>
```