

School of Information Technology and Engineering

Lab Final Assessment Test, JUNE 2021 B.Tech., Winter-2020-2021

NAME	PRIYAL BHARDWAJ
REG. NO.	18BIT0272
COURSE CODE	CSE3502
COURSE NAME	INFORMATION SECURITY MANAGEMENT
SLOT	L39+L40
FACULTY	Prof. I SUMAIYA THASEEN


Google Drive Link:

https://drive.google.com/drive/folders/18j1KD0x2nBwBYt9oaLvWFvgo-RSNKcxH?usp=sharing


Q.1 NOTE: I have changed the IPs of DNS server as well.


i)

18BIT0272 PRIYAL BHARDWAJ




ii)






iii)







- - ×



Х Config CLI Attributes Physical

IOS Command Line Interface

```
ASA(config)#int gl/l
ASA(config-if) #no ip address
ASA(config-if)#no nameif
ASA(config-if) #no security-level
ASA(config-if)#int g1/2
ASA(config-if) #no nameif
ASA(config-if) #no security-level
ASA(config-if) #no ip address dhcp
ASA(config-if)#exit
ASA(config) #show run
: Saved
ASA Version 9.6(1)
hostname ASA
enable password 4IncP7vTjpaba2aF encrypted
names
interface GigabitEthernet1/1
no nameif
no security-level
no ip address
interface GigabitEthernet1/2
 no nameif
 no security-level
no ip address
interface GigabitEthernet1/3
no nameif
no security-level
no ip address
shutdown
interface GigabitEthernet1/4
no nameif
no security-level
no ip address
shutdown
interface GigabitEthernet1/5
no nameif
 no security-level
no ip address
shutdown
interface GigabitEthernet1/6
no nameif
no security-level
no ip address
<---> More --->
```

a) Configured security levels 0 and 100 for outside and inside respectively on ASA



Physical Config CLI Attributes

IOS Command Line Interface

```
ASA(config)#int gl/l
ASA(config-if)#ip address 20.1.1.1 255.255.255.252
ASA(config-if) #nameif outside
INFO: Security level for "outside" set to 0 by default.
ASA(config-if)#security-level 0
ASA(config-if) #no shut-
ASA(config-if)#int g1/2
ASA(config-if)#ip address 172.68.1.1 255.255.255.0
ASA(config-if) #nameif inside
INFO: Security level for "inside" set to 100 by default.
ASA(config-if) #security-level 100
ASA(config-if) #no shut
ASA(config-if)#exit
ASA(config) #show int ip brief
Interface
                                 OK? Method Status
                      IP-Address
Protocol
Virtual0
                      127.1.0.1
                                     YES unset up
GigabitEthernet1/1
                     20.1.1.1
                                     YES manual up
GigabitEthernet1/2
                      172.68.1.1
                                     YES manual up
up
GigabitEthernet1/3
                      unassigned
                                     YES unset
administratively down down
GigabitEthernet1/4
                                    YES unset
                      unassigned
administratively down down
GigabitEthernet1/5
                      unassigned
                                     YES unset
administratively down down
GigabitEthernet1/6
                      unassigned
                                     YES unset
administratively down down
GigabitEthernet1/7
                      unassigned
                                     YES unset
administratively down down
GigabitEthernet1/8
                                     YES unset
                      unassigned
administratively down down
Management1/1
                      unassigned
                                     YES unset down
down
Internal-Controll/1 127.0.1.1
                                     YES unset up
Internal-Data1/1
                     unassigned
                                     YES unset up
Internal-Data1/2
                      unassigned
                                     YES unset up
Internal-Data1/3
                unassigned
                                     YES unset up
up
ASA(config)#
```

b) DHCP Server configuration

IP address range 172.68.1.10-172.68.1.20


```
ASA(config) #dhcp address 172.68.1.10-172.68.1.20 inside

ASA(config) #dhcp dns 10.10.10.10

ASA(config) #dhcp option 3 ip 172.68.1.1

ASA(config) #dhcp enable inside
```

After DHCP configuration new IPs of PC-A and PC-B



IP address of PC-A was already set as 172.68.1.10 so it is same but IP address of PC-B has changed from 172.68.1.20 to 172.68.11

c) NAT object

```
ASA(config) #route outside 0.0.0.0 0.0.0.0 20.1.1.2


ASA(config) #object network INSIDE-NET

ASA(config-network-object) #subnet 172.68.1.0 255.255.255.0


ASA(config-network-object) #nat (inside, outside) dynamic interface

ASA(config-network-object) #exit
```

Ping from PC-A to default gateway i.e. 172.68.1.1 is successful




v) ASA policy map and inspection policies configuration




We can see them in show run now

```
!
class-map inspection_default
match default-inspection-traffic
!
policy-map global_policy
class inspection_default
inspect icmp
!
service-policy global_policy global
!
```

Ping from PC-A to dhcp dns server successful:



Web browser access on PC-B failed:




Now we inspect http policy in ASA:



```
class-map inspection_default
  match default-inspection-traffic
!
policy-map global_policy
  class inspection_default
   inspect http
  inspect icmp
!
service-policy global_policy global
```


Now web browser access is successful:



Pinging www.ccnasecurity.com is unsuccessful at first:



Then we inspect dns policy in ASA and it is successful:



Vulnerable Site: http://testphp.vulnweb.com/

Ping:

```
C:\Users\PRIYAL BHARDWAJ>ping testphp.vulnweb.com


Pinging testphp.vulnweb.com [18.192.172.30] with 32 bytes of data:
Reply from 18.192.172.30: bytes=32 time=144ms TTL=50
Reply from 18.192.172.30: bytes=32 time=144ms TTL=50
Reply from 18.192.172.30: bytes=32 time=144ms TTL=50
Reply from 18.192.172.30: bytes=32 time=146ms TTL=50

Ping statistics for 18.192.172.30:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 144ms, Maximum = 146ms, Average = 144ms
```

IP Address of http://testphp.vulnweb.com/ is 18.192.172.30

Arachni is a Free/Public-Source Web Application Security Scanner that can be **used to** create automated security reports for your website as it evolves.


Downloaded the exe file and then installed Arachni in my system:




After launching arahni_web.bat from cmd it started listening on tcp://localhost:9292.

```
::\Users\PRIYAL BHARDWAJ\Downloads\arachni-1.5.1-0.5.12-windows-x86_64\bin>arachni_web.bat
Puma 2.14.0 starting...
 Min threads: 0, max threads: 16
 Environment: development
 Listening on tcp://localhost:9292
```


Signed in to arachni using given user credentials and made a New Scan:



Scanned the website for about 9 minutes and got 42 issues:



Closer look at the issues logged:




```
Excitions/specific proposalion. All rights reserved.
(c) Ricrosoff Corporation. All rights reserved.
(d) Ricrosoff Corporation. All rights reserved.

**Ricrosoff Corporation. All rights.


**Ricrosoff Corporation. All ricrosoff Corporation. All ricrosoff Corporation. All ricrosoff Corporation.

**Ricrosoff Corporation. All ricrosoff Corporatio
```


We can find a detailed description of the issues logged on Arachni along with CWE link to see solutions for that vulnerability:



SQL Injection CWE Screenshot:



Potential Mitigations:



CWE Link: http://cwe.mitre.org/data/definitions/89.html