

Mini Crest

Self Priming Regenerative Pump



Features

- High Quality & long life Mechanical Seal
- Forged Brass Impeller
- Compact & sleek look
- Fitted with thermal over load protector



Applications

- Bungalows, apartments, hotels, farmhouses, laundries, Clubs
- Gardening and Lawn Sprinklers
- Lifting water to overhead storage tanks
- Water Circulation in industries

Standard Specifications

- Range : 0.37 kW to 0.75 kW (0.5 HP to 1.0 HP)
- Pipe Size : 25 x 25 mm
- Total Head : Upto 34 meters
- Capacity : Upto 2700 LPH
- Liquid : Clear and cold water
- Rotation : Clockwise as viewed from motor end
- Operating temperature : Suitable upto 65° C water
- Voltage Band : 180 to 240 volts

Performance chart for Mini Crest Series Pump at 220 volts, 1PH, 50 Hz AC Supply

Rating	Motor		Pipe Size SucxDel (mm)	Head in Meters							
				6	9	12	18	21	27	30	34
	kW	HP		Discharge in LPH							
 MINI CREST II	0.37	0.5	25 x 25	1950	1800	1400	950	450			
 MINI CREST I	0.75	1.0	25 x 25	2700	2550	2250	1950	1700	1250	1050	750

Note : The motor ratings in HP are only indicative and for reference purpose



After Sales Service Helpline 1800-419-0505

Registered Office

Equinox Business Park, 1st Floor, Tower 3, East Wing,
LBS Marg, Kurla (W), Mumbai 400070, India
W: www.crompton.co.in
CIN No.: L31900MH2015PLC262254

Crompton Greaves Consumer Electricals Limited Pumps Division

Plot No. C-19, MIDC, Ahmednagar 414 111
T: +91 241 6606 500