

SEABORN Histogram

If you have numeric type dataset and want to visualize in histogram then the **seaborn histogram** will help you. For this **seaborn distplot** function responsible to plot it.

Load DataFrame from GitHub

To load the dataset from [GitHub seaborn repository](#) use **sns.load_dataset()** function.

```
import seaborn as sns
from scipy.stats import norm
import matplotlib.pyplot as plt
tips_df=sns.load_dataset('tips')
tips_df
```

Observe above **tips DataFrame (tips_df)**, Which contain three numeric type column like 'tips_bill', 'tip' and 'size'. So, we can plot a histogram for them.

```
sns.distplot(tips_df["size"])
```

Plot tips_df["tip"] Histogram

```
sns.distplot(tips_df["tip"])
```

Plot tips_df["total_bill"] Histogram

```
sns.distplot(tips_df["total_bill"])
```

How to modify the seaborn histogram?

Seaborn distplot function has a bunch of parameters, which help to decorate sns histogram.

- **a:** Pass numeric type data as a Series, 1d-array, or list to plot histogram. Examples showed above.
- **bins:** If, the dataset contains data from range 1 to 55 and your requirement to show data step of 5 in each bar.

```
▪ sns.distplot(tips_df["total_bill"], bins=55)
```

- **hist:** If, you don't need histogram then pass bool **"True"** value otherwise **"False"**.

SEABORN Histogram

- `sns.distplot(tips_df["total_bill"], hist = False)`

- **kde:** ked stands for “kernel density estimate” to show it pass bool value “True” or “False”.

```
sns.distplot(tips_df["total_bill"], kde=False,)
```

- **rug:** To show rug plot pass bool value “True” otherwise “False”.

```
sns.distplot(tips_df["total_bill"], rug=True,)
```

- **color:** To give color for sns histogram, pass a value in as a string in hex or color code or name.

- `sns.distplot(tips_df["total_bill"], color="r",)`

- **vertical:** To show histogram vertical pass bool value “False” and **horizontal** “True”.

- `sns.distplot(tips_df["total_bill"], vertical=True,)`