

**Ex. No.: 8****Date:26.03.2025****PRODUCER CONSUMER USING SEMAPHORES**

**Aim:** To write a program to implement a solution to producer consumer problem using semaphores.

**Algorithm:**

1. Initialize semaphore empty, full and mutex.
2. Create two threads- producer thread and consumer thread.
3. Wait for target thread termination.
4. Call sem\_wait on empty semaphore followed by mutex semaphore before entry into critical section.
5. Produce/Consume the item in critical section.
6. Call sem\_post on mutex semaphore followed by full semaphore
7. before exiting critical section.
8. Allow the other thread to enter its critical section.
9. Terminate after looping ten times in producer and consumer Threads each.

**Program Code:**

```
#include <stdio.h>
#include <stdlib.h>
int mutex = 1; // Initialize a mutex to 1
int full = 0; // Number of full slots as 0
int empty = 10, x = 0; // Number of empty slots as size of buffer
void producer()
{
    // Decrease mutex value by 1
    --mutex;
    // Increase the number of full
    // slots by 1
    ++full;
    // Decrease the number of empty
    // slots by 1
    --empty;
    // Item produced
    x++;
    printf("\nProducer produces"
    "item %d",
    x);
```

```

        // Increase mutex value by 1
        ++mutex;
    }

// Function to consume an item and
// remove it from buffer
void consumer()
{
    // Decrease mutex value by 1
    --mutex;

    // Decrease the number of full
    // slots by 1
    --full;

    // Increase the number of empty
    // slots by 1
    ++empty;
    printf("\nConsumer consumes "
        "item %d",
        x);
    x--;

    // Increase mutex value by 1
    ++mutex;
}

// Driver Code
int main()
{
    int n, i;
    printf("\n1. Press 1 for Producer"
        "\n2. Press 2 for Consumer"
        "\n3. Press 3 for Exit");

    // Using '#pragma omp parallel for'
    // can give wrong value due to
    // synchronization issues.

    // 'critical' specifies that code is
    // executed by only one thread at a
    // time i.e., only one thread enters
    // the critical section at a given time
    #pragma omp critical

        for (i = 1; i > 0; i++) {

```

```

printf("\nEnter your choice:");
scanf("%d", &n);

// Switch Cases
switch (n) {
case 1:

// If mutex is 1 and empty
// is non-zero, then it is
// possible to produce
if ((mutex == 1)
    && (empty != 0)) {
    producer();
}

// Otherwise, print buffer
// is full
else {
    printf("Buffer is full!");
}
break;

case 2:

// If mutex is 1 and full
// is non-zero, then it is
// possible to consume
if ((mutex == 1)
    && (full != 0)) {
    consumer();
}

// Otherwise, print Buffer
// is empty
else {
    printf("Buffer is empty!");
}
break;

// Exit Condition
case 3:
exit(0);
break;
}
}

```

}

## OUTPUT:

```
(student@kali)-[~]  
$ vi semaphore.c  
  
(student@kali)-[~] document will  
$ gcc semaphore.c -o semaphore  
  
(student@kali)-[~]  
$ ./semaphore  
  
1. Press 1 for Producer  
2. Press 2 for Consumer  
3. Press 3 for Exit  
Enter your choice:1  
  
Producer produces item 1  
Enter your choice:1  
  
Producer produces item 2  
Enter your choice:1  
  
Producer produces item 3  
Enter your choice:1  
Buffer is full!  
Enter your choice:2  
  
Consumer consumes item 3  
Enter your choice:2  
  
Consumer consumes item 2  
Enter your choice:2  
  
Consumer consumes item 1  
Enter your choice:2  
Buffer is empty!  
Enter your choice:3
```

## RESULT:

Hence, producer consumer using semaphores has been executed successfully.