

MongoDB + PyMongo Example Queries

- Make sure your MongoDB container is running
- Make sure you have pymongo installed before running cells in this notebook. If not, use `pip install pymongo`.

```
In [ ]: import pymongo
        from bson.json_util import dumps

        # --> Update the URI with your username and password <--

        uri = "mongodb://username:password@localhost:27017"
        client = pymongo.MongoClient(uri)
        mflixdb = client.mflix
```

```
In [ ]: # Setup DemoDB with 2 collections
        demodb.customers.drop()
        demodb.orders.drop()

        customers = [
            {"custid": "C13", "name": "T. Cruise", "address": { "street": "201 Main S
            {"custid": "C25", "name": "M. Streep", "address": { "street": "690 River
            {"custid": "C31", "name": "B. Pitt", "address": { "street": "360 Mountair
            {"custid": "C35", "name": "J. Roberts", "address": { "street": "420 Greer
            {"custid": "C37", "name": "T. Hanks", "address": { "street": "120 Harbor
            {"custid": "C41", "name": "R. Duvall", "address": { "street": "150 Market
            {"custid": "C47", "name": "S. Loren", "address": { "street": "Via del Cor
        ]

        orders = [
            { "orderno": 1001, "custid": "C41", "order_date": "2017-04-29", "ship_dat
            { "orderno": 1002, "custid": "C13", "order_date": "2017-05-01", "ship_dat
            { "orderno": 1003, "custid": "C31", "order_date": "2017-06-15", "ship_dat
            { "orderno": 1004, "custid": "C35", "order_date": "2017-07-10", "ship_dat
            { "orderno": 1005, "custid": "C37", "order_date": "2017-08-30", "items":
            { "orderno": 1006, "custid": "C41", "order_date": "2017-09-02", "ship_dat
            { "orderno": 1007, "custid": "C13", "order_date": "2017-09-13", "ship_dat
            { "orderno": 1008, "custid": "C13", "order_date": "2017-10-13", "items":
        ]

        demodb.customers.insert_many(customers)
        demodb.orders.insert_many(orders)

        numCustomers = demodb.customers.count_documents({})
        numOrders = demodb.orders.count_documents({})

        print(f'There are {numCustomers} customers and {numOrders} orders')
```

```
In [ ]: # The key (_id) attribute is automatically returned unless you explicitly sa
```

```
# SELECT name, rating FROM customers
data = demodb.customers.find({}, {"name":1, "rating":1})
print(dumps(data, indent=2))
```

In []: *# Now without the _id field.*

```
# SELECT name, rating FROM customers
data = demodb.customers.find({}, {"name":1, "rating":1, "_id":0})
print(dumps(data, indent=2))
```

All fields EXCEPT specific ones returned

In []: *# For every customer, return all fields except _id and address.*

```
data = demodb.customers.find({}, {"_id": 0, "address": 0})
print(dumps(data, indent=2))
```

Equivalent to SQL LIKE operator

In []: *# SELECT name, rating FROM customers WHERE name LIKE 'T%'*

```
# Regular Expression Explanation:
# ^ - match beginning of line
# T - match literal character T (at the beginning of the line in this case)
# . - match any single character except newline
# * - match zero or more occurrences of the previous character (the . in this case)

data = demodb.customers.find({"name": {"$regex": "^T.*"}}, {"_id": 0, "name": 1})
print(dumps(data, indent=2))
```

Sorting and limiting

In []: *# SELECT name, rating FROM customers ORDER BY rating LIMIT 2*

```
data = demodb.customers.find( { }, {"_id": 0, "name": 1, "rating":1} ).sort(
print(dumps(data, indent=2))
```

In []: *# Same as above, but sorting in DESC order*

```
# SELECT name, rating FROM customers ORDER BY rating DESC LIMIT 2
```

```
data = demodb.customers.find( { }, {"_id": 0, "name": 1, "rating":1} ).sort(
print(dumps(data, indent=2))
```

In []: *# Providing 2 sort keys...*

```
data = demodb.customers.find( { }, {"_id": 0, "name": 1, "rating":1} ).sort(
print(dumps(data, indent=2))
```

Your Turn with mflix DB

Question 1

```
In [16]: # How many Users are there in the mflix database? How many movies?
```

Question 2

```
In [ ]: # Which movies have a rating of "TV-G"? Only return the Title and Year.
```

Question 3

```
In [ ]: # Which movies have a runtime of less than 20 minutes? Only return the title
```

Question 4

```
In [ ]: # How many theaters are in MN or MA?
```

Question 5

```
In [ ]: # Give the names of all movies that have no comments yet. Make sure the name
```

Question 6

```
In [ ]: # Return a list of movie titles and all actors from any movie with a title t  
# Sort the list by title.
```