

DOM EVENT

DOM Events

Events are signals that something has occurred. (user inputs / actions)

DOM Events

onclick (when an element is clicked)

onmouseenter (when mouse enters an element)

Event Listener

addEventListener

element.addEventListener(event, callback)

```
btn.addEventListener("click", function () {  
  console.log("button clicked");  
});
```

```

JS app.js > box.addEventListener("mouseenter") callback
1   let p = document.querySelector("p");
2
3   p.addEventListener("click", function () {
4     console.log("parah was clicked");
5   });
6
7   let box = document.querySelector(".box");
8   box.addEventListener("mouseenter", function () {
9     console.log("mouse inside box");
10  });
11

```

this in Event Listeners

When 'this' is used in a callback of event handler of something, it refers to that something.

```

app.js > btn.addEventListener("click") callback
    let btn = document.querySelector("button");

    btn.addEventListener("click", function () {
      console.dir(this.innerText);
      this.style.backgroundColor = "blue";
    });

```

```

JS app.js > ...
1   let btn = document.querySelector("button");
2   let p = document.querySelector("p");
3   let h1 = document.querySelector("h1");
4   let h3 = document.querySelector("h3");
5
6   function changeColor() {
7     console.dir(this.innerText);
8     this.style.backgroundColor = "blue";
9   }
10
11  btn.addEventListener("click", changeColor);
12
13  p.addEventListener("click", changeColor);
14
15  h1.addEventListener("click", changeColor);
16
17  h3.addEventListener("click", changeColor);
18

```

KeyBoard Event

```
app.js > ...  
let inp = document.querySelector("input");  
      
inp.addEventListener("keydown", function (event) {  
  console.log("key = ", event.key);  
  console.log("code = ", event.code);  
  console.log("key was pressed");  
});  
  
// inp.addEventListener("keyup", function () {  
//   console.log("key was released");  
// });
```

More Events

change event

The change event occurs when the value of an element has been changed (only works on <input>, <textarea> and <select> elements).

input event

The input event fires when the value of an <input>, <select>, or <textarea> element has been changed.

```
JS app.js > user.addEventListener("input") callback
1  let form = document.querySelector("form");
2
3  form.addEventListener("submit", function (event) {
4    event.preventDefault();
5  });
6
7  let user = document.querySelector("#user");
8
9  user.addEventListener("change", function () {
10     console.log("change event");
11     console.log("final value = ", this.value);
12 });
13
14 user.addEventListener("input", function () {
15     console.log("input event");
16     console.log("final value = ", this.value);
17 });
18
```