PIZZA SALES ANALYSIS

```
create database project_pizza;

use project_pizza;
```

Retrieve the total number of orders placed.

```
select count(*) as Total_Orders from `orders (1)`;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

Total_Orders
21350

2. Calculate the total revenue generated from pizza sales.

```
create view sales_info as
select od.*,(od.quantity * p.price) as Sales
from order_details od
join pizzas p on od.pizza_id=p.pizza_id;
select concat("$",round(sum(sales),2)) as Total_Sales from sales_info;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

Total_Sales
$817860.05

3. Identify the highest-priced pizza.

```
select pt.name,p.price
from pizza_types pt
join pizzas p on pt.pizza_type_id=p.pizza_type_id
where p.price=(select max(price) from pizzas p);
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

name	price
The Greek Pizza	35.95

4. Identify the most common pizza size ordered.

```
select size,count(pizza_id) as total_orders from pizzas group by size
order by total_orders desc limit 1;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

size	total_orders
S	32

5. List the top 5 most ordered pizza types along with their quantities.

```
create view quantity as
select t.name, sum(od.quantity) as total_quantity
from pizzas p
join pizza_types t
```

```
on p.pizza_type_id = t.pizza_type_id
join order_details od
on od.pizza_id = p.pizza_id
group by t.name
order by total_quantity desc
limit 5;
select * from quantity;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

name	total_quantity
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

6. Join the necessary tables to find the total quantity of each pizza category ordered.

```
select t.category,sum(od.quantity) as Total_Quantity
from pizzas p
join pizza_types t
on p.pizza_type_id=t.pizza_type_id
join order_details od
on od.pizza_id=p.pizza_id
group by t.category;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

category	Total_Quantity
Classic	14888
Veggie	11649
Supreme	11987
Chicken	11050

7.Determine the distribution of orders by hour of the day.

```
select hour(time) as order_hour,count(order_id) as Total_orders
from `orders (1)`
group by order_hour
order by order_hour;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

order_hour	Total_orders
9	1
10	8
11	1231
12	2520
13	2455
14	1472
15	1468
16	1920
17	2336
18	2399
19	2009
20	1642
21	1198
22	663
23	28

8 Join relevant tables to find the category-wise distribution of pizzas.

```
select category,count(pizza_type_id) as Total_Pizza
from pizza_types
group by category
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

category	Total_Pizza
Chicken	6
Classic	8
Supreme	9
Veggie	9

9. Group the orders by date and calculate the average number of pizzas ordered per day.

```
select o.date,avg(od.quantity) as Total_Average
from `orders (1)`o
join order_details od
on o.order_id=od.order_id
group by o.date;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

date	Total_Average
2015-01-01	1.0062
2015-01-02	1.0313
2015-01-03	1.0260
2015-01-04	1.0000
2015-01-05	1.0331
2015-01-06	1.0208
2015-01-07	1.0376
2015-01-08	1.0117
2015-01-09	1.0325
2015-01-10	1.0069
2015-01-11	1.0175
2015-01-12	1.0085

10 Determine the top 3 most ordered pizza types based on revenue.

```
select t.name,sum(od.quantity * p.price) as revenue
from pizzas p
join pizza_types t
```

```
on p.pizza_type_id=t.pizza_type_id
join order_details od
on od.pizza_id=p.pizza_id
group by t.name
order by revenue desc
limit 3;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5

11. Calculate the percentage contribution of each pizza type to total revenue.

```
select t.name,
round(sum(od.quantity * p.price) * 100 /
(select sum(od1.quantity * p1.price)
from order_details od1
join pizzas p1
on od1.pizza_id = p1.pizza_id), 2) as percentage
from pizzas p
join pizza_types t
on p.pizza_type_id = t.pizza_type_id
join order_details od
on od.pizza_id = p.pizza_id
group by t.name;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

name	percentage
The Hawaiian Pizza	3.95
The Classic Deluxe Pizza	4.67
The Five Cheese Pizza	3.19
The Italian Supreme Pizza	4.09
The Mexicana Pizza	3.27
The Thai Chicken Pizza	5.31
The Prosciutto and Arugula Pizza	2.96
The Barbecue Chicken Pizza	5.23
The Greek Pizza	3.48
The Spinach Supreme Pizza	1.87
The Green Garden Pizza	1.71
The Italian Capocollo Pizza	3.07
The Spicy Italian Pizza	4.26
The Spinach Pesto Pizza	1.91
The Vegetables + Vegetables Pi...	2.98
The Southwest Chicken Pizza	4.24
The California Chicken Pizza	5.06
The Pepperoni Pizza	3.69

12. Analyze the cumulative revenue generated over time.

```
select date,
sum(daily_revenue) over(order by date) as cumulative_revenue
from(
select o.date, sum(od.quantity * p.price) as daily_revenue
from orders o
join order_details od
on o.order_id = od.order_id
join pizzas p
on od.pizza_id = p.pizza_id
group by o.date
) as sales;
```

date	cumulative_revenue
2015-01-01	2713.8500000000004
2015-01-02	5445.75
2015-01-03	8108.15
2015-01-04	9863.6
2015-01-05	11929.55
2015-01-06	14358.5
2015-01-07	16560.7
2015-01-08	19399.05
2015-01-09	21526.4
2015-01-10	23990.350000000002
2015-01-11	25862.65

8108.15

13 Determine the top 3 most ordered pizza types based on revenue for each pizza category.

```
select t.category,sum(od.quantity * p.price) as revenue
from pizzas p
join pizza_types t
on p.pizza_type_id=t.pizza_type_id
join order_details od
on od.pizza_id=p.pizza_id
group by t.category
limit 3;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

category	revenue
Classic	220053.1000000001
Veggie	193690.45000000298
Supreme	208196.99999999822