

- Operator Stack (op) -> Stores operators (+, -, *, /, (,)) and ensures precedence is maintained.

Code Workflow:

- 1. Read the expression from left to right.
- 2. If a digit is found, push it into the val stack as a string.
- 3. If an operator is found:
 - If '(' is encountered, push it onto op stack.
 - If ')' is encountered, pop and evaluate everything inside the brackets.
 - If it has higher precedence than the top of op stack, push it.
 - If lower precedence, pop from op and evaluate until precedence rule is satisfied.
- 4. After loop ends, evaluate remaining operators.
- 5. The final result stored in val.top() contains the prefix expression.

2. Dry Run & Step-by-Step Test Case Explanations

Test Case 1:

Expression: "1+(2+6)*4/8-3"

Expected Output (Prefix): "-+1/*+26483"

Step-by-Step Execution:

- 1. Read '1' -> Operand -> Push to val stack -> val = ["1"]
- 2. Read '+' -> Operator -> Push to op stack -> op = ['+']
- 3. Read '(' -> Push to op stack -> op = ['+', '(')]
- 4. Read '2' -> Operand -> Push to val -> val = ["1", "2"]
- 5. Read '+' -> Operator -> Push to op stack -> op = ['+', '(', '+']
- 6. Read '6' -> Operand -> Push to val -> val = ["1", "2", "6"]
- 7. Read ')' -> Evaluate (2+6) -> Pop '+' and combine "2" and "6" -> "+26" -> val = ["1", "+26"]
- 8. Read '*' -> Push to op -> op = ['+', '*']
- 9. Read '4' -> Operand -> Push to val -> val = ["1", "+26", "4"]
- 10. Read '/' -> Push to op -> op = ['+', '*', '/']
- 11. Read '8' -> Operand -> Push to val -> val = ["1", "+26", "4", "8"]
- 12. Read '-' -> Pop and evaluate '/' -> "*+264" -> val = ["1", "/*+264", "8"]
- 13. Pop and evaluate '*' -> "/*+2648" -> val = ["1", "/*+2648"]
- 14. Pop and evaluate '+' -> "+1/*+2648" -> val = ["+1/*+2648"]
- 15. Read '3' -> Operand -> Push to val -> val = ["+1/*+2648", "3"]
- 16. Evaluate '-' -> Final result: "-+1/*+26483"

Summary & Notes:

- Uses two stacks (val & op) for infix to prefix conversion.
- Handles operator precedence correctly.
- Brackets are processed in the right order.
- Final prefix expression stored in val.top().

Key Concepts:

- Two Stack Approach -> val (operands), op (operators).
- Operator Precedence -> * and / > + and -.
- Bracket Handling -> '(' push hota hai, ')' pe evaluation hoti hai.
- Final Evaluation -> Remaining operators are processed at the end.

Common Mistakes & Fixes:

- priority() should return 0 by default.
- Bracket handling must be implemented correctly.
- The code currently supports only single-digit numbers (multi-digit support can be added).
