

# Zig-Zag Recursion Quick Revision Notes

Logic of the Given Code:

- The function `zig(int n)` prints numbers in a "zig-zag" pattern using recursion.
- **\*\*Base Condition\*\***:
  - If `n == 0`, return `0` to stop further recursion.
- **\*\*Recursive Calls\*\***:
  - First, print `n` before calling `zig(n-1)` (pre-recursive call).
  - After returning from the first recursive call, print `n` again (mid-print).
  - Then call `zig(n-1)` again (post-recursive call).
  - Finally, print `n` once more after the second recursive call.
- This results in a symmetrical "zig-zag" pattern of numbers.

```
#include<iostream>
using namespace std;

// Function to print zig-zag pattern using recursion
int zig(int n){
    if(n == 0) return 0; // Base case: Stop recursion when n reaches 0

    cout << n; // Pre-recursive print
    zig(n-1); // First recursive call
    cout << n; // Mid-recursive print
    zig(n-1); // Second recursive call
    cout << n; // Post-recursive print
}

int main(){
    zig(4); // Calling function for n = 4
}
```

## Dry Run of the Code (For zig(2))

Function Call | Output

```
-----|-----
zig(2)   | 2 (pre)
zig(1)   | 1 (pre)
```

```
zig(0)    | - (base case)
          | 1 (mid)
zig(0)    | - (base case)
          | 1 (post)
          | 2 (mid)
zig(1)    | 1 (pre)
zig(0)    | - (base case)
          | 1 (mid)
zig(0)    | - (base case)
          | 1 (post)
          | 2 (post)
```

### Final Output for zig(2):

2 1 1 1 2 1 1 1 2

### Time Complexity:

- Each function call makes two more recursive calls.
- This results in  $O(2^n)$  time complexity.

### Key Takeaways:

- This function prints numbers in a symmetrical "zig-zag" order.
- It follows a **pre, mid, and post recursion** pattern.
- The number of recursive calls grows exponentially, making it inefficient for large values.