```
import { randomUUID } from "node:crypto";
import { getAuthenticatedUser, db } from
"./_auth.js";

export default async function handler(req,
res) {
  if (req.method !== "POST") {
    res.setHeader("Allow", "POST");
    return res.status(405).json({ success:
false, message: "Method not allowed" });
  }

  try {
    const auth = await
getAuthenticatedUser(req);
    if (!auth || !auth.uid) {
      return res.status(401).json({
success: false, message: "Please log in
first" });
    }

    const merchantKey =
process.env.OXAPAY_MERCHANT_API_KEY;
    if (!merchantKey) {
      return res.status(500).json({
success: false, message: "Payment
configuration is missing" });
    }

    // Amount comes from the client but is
```

```
validated on the server.
    const requested = Number(req.body &&
req.body.amount);
    if (!Number.isFinite(requested) ||
requested < 1 || requested > 100000) {
      return res.status(400).json({
        success: false,
        message: "Amount must be between 1
and 100,000 USDT",
      });
    }
    const amount = Math.round(requested *
100) / 100;
    const orderId = "NRD_" + randomUUID();

    const baseUrl = process.env.SITE_URL ||
"https://noir-vip.vercel.app";
    const sandbox =
process.env.OXAPAY_SANDBOX === "true";

    const database = db();
    const orderRef =
database.ref("depositOrders/" + orderId);

    await orderRef.set({
      orderId,
      uid: auth.uid,
      amount,
      currency: "USDT",
      status: "creating",
      createdAt: Date.now(),
    });

    const response = await
```

```
fetch("https://api.oxapay.com/v1/payment/in
voice", {
      method: "POST",
      headers: {
        merchant_api_key: merchantKey,
        "Content-Type": "application/json",
      },
      body: JSON.stringify({
        amount,
        currency: "USDT",
        lifetime: 30,
        order_id: orderId,
        description: "NOIR wallet deposit",
        callback_url: baseUrl +
"/api/oxapay-webhook",
        return_url: baseUrl,
        sandbox,
      }),
    });

    const result = await
response.json().catch(() => ({}));

    if (!response.ok || !result.data ||
!result.data.payment_url ||
!result.data.track_id) {
      await orderRef.update({ status:
"invoice_failed", updatedAt: Date.now() });
      console.error("OxaPay invoice request
failed", {
        httpStatus: response.status,
        error: result.error ||
result.message || "Unknown error",
      });
```

```
      return res.status(502).json({
success: false, message: "Could not create
payment invoice" });
    }

    await orderRef.update({
      status: "pending",
      trackId:
String(result.data.track_id),
      paymentUrl: result.data.payment_url,
      updatedAt: Date.now(),
    });

    return res.status(200).json({
      success: true,
      orderId,
      amount,
      currency: "USDT",
      paymentUrl: result.data.payment_url,
    });
  } catch (error) {
    console.error("NOIR deposit error:",
error.message);
    return res.status(500).json({ success:
false, message: "Unable to create deposit
invoice" });
  }
}
```